

Front View



Rear View



Features

- Socket 988B, Socket 3rd Generation Intel® Core™ i3/i5/i7 up to 45W
- 204-pin Dual Channel DDR3 1066/1333/1600 MHz SODIMM x 2 (Up to 8GB)
- Intel® Integrated Graphics Engine Supports DP, HDMI, VGA, DVI
- LAN 1: Intel® PHY WG82579LM Gigabit Ethernet
LAN 2: Realtek RTL 8111E Gigabit Ethernet
- Up to 2.5" HDD/SSD Bay x 2
- USB 2.0 x 2, USB 3.0 x 4 (USB3.0 Supported by Win7)
- COM x 2 (Optional 5 Ports)
- Mini-PCIe Socket x 1, CFast™ x 1, TPM
- Mini Size 195mm(W) x 70mm(H) x 220mm(D)




Specifications

CPU	Socket G2 (rPGA988B) 3rd Generation for Intel® Core™ i7 / i5 / Celeron® QC / DC processors up to 45W Max
Chipset	Intel® QM77
System Memory	204-pin Dual Channel DDR3 1066/1333/1600 MHz SODIMM x2 (up to 16GB)
Display Interface	VGA x 1
	DVI-D x 1
	Others: HDMI x 1, DP x 1
Storage Device	SSD CFast™ x 1
	HDD 2.5" SATA HDD Bay x 2
Network	LAN Gigabit Ethernet
	Wireless Optional by Mini Card
Front I/O	USB Host USB2.0 x 2
	LAN —
	Serial Port —
	DIO —
	Audio —
Rear I/O	KB/MS —
	Others —
	USB Host USB3.0 x 4
	LAN RJ-45 x 2
	Serial Port RS-232/422/485 x 1; RS-232 x 1
Expansion	DIO Optional COM Module for COM2~COM6 (RS-232)
	Audio Mic-in, Lin-in, Line-out
	KB/MS KB/MS x 2
	Others Power input x 1
	PCIe —
Indicator	PCI —
	Mini Card Mini Card x 1
	Mini PCI —
	Others —
Power Requirement	Front PWR, HDD
	Rear —
Power Consumption	12V DC-in
System Cooling	CPU cooler x 1 System Cooler x 1
Mounting	Optional Wall mount
Operating temperature	32°F ~ 113°F (0°C ~ 45°C)
Storage Temperature	-4°F ~ 140°F (-20°C ~ 60°C)
Anti-Vibration	0.5g rms/ 5 ~ 500Hz/ operation – HDD type
Anti-Shock	15 G peak acceleration (11 msec. duration)
Watchdog Timer	1~255 step by software programming
MTBF (Hours)	60,000
Certification	EMC CE/ FCC class A
	Safety —
Dimension (W x H x D)	7.68" x 2.76" x 8.66" (195mm x 70mm x 220mm)
Gross Weight	—

AIS-E2

Dimension

Unit: mm



Ordering Information

Part Number	Chipset	RAM	Cooler	Storage	Display	LAN	USB	RS-232	RS-232/422/485	KB/MS	Audio	DIO	Expansion Slot	Mounting	Power
AIS-E2-QM77-001	Intel® QM77	SODIMM	Fan	2.5" HDD Bay x 1	VGA, DVI-D, HDMI, DP	GbE x 2	USB 2.0 x 2 USB 3.0 x 4	1	1	Yes	Mic-in, Line-in, Line-out	—	Mini-PCIe x 1 CF-SATA x 1	Desktop	DC

Packing List

- Gift Box 9761E20000 x 1 (Including 84W Power Adapter, CPU Cooler)
- DVD-ROM for Manual (in PDF Format) and Drivers
- AIS-E2

Optional Accessories

- COM Port Module for COM2 ~ COM6
- Wallmount Bracket
- 2.5" HDD Bay Bracket