

Expandable Portable Computing Solution

HT II-713



HTII-713

- ✓ **Enormous capacity, speedy engine**
- ✓ **Expandable and more flexible removable drives**
- ✓ **Super Brilliant TFT LCD screen**

The new released HTII-713, is the unpredictably powerful choice for workstation or server. The design of three 5.25" drives and two 3.5" drives makes HTII-713 the "Power of Standards." Its 7-slot design is capable to accommodate any ATX size motherboards. A selection of 14", 15", or 17" super brilliant TFT LCD screen designed with an adjustable angle, allows users to fully enjoy the beauty of true colors. The new RJ-45 cabling style fits in users' "pack-and-go" modern life style, in order to avoid unnecessary detachment of cable from the computer unit. An arch design of the handle and the fine-texture coating of flash gray also draw HTII-713 a perfect appearance.

Host Applications:

- Portable Unix Database Servers
- Mobile Internet & Web Servers
- Multimedia Applications
- PLC Programming
- Onsite Training



www.acmeportable.com
info@acmeportable.com

HT II-713 Specification

Model No.	HTII-713
Motherboard	ATX
Slot	7
Drive Bay	3 x 5.25" (open) 2 x 3.5"(open)
Color	Flash Gray
LCD	14.1", 15.1",15.4" (Tiltable), 17" (None Tiltable) 14.1"--15.4" LCD, up to 350 nits brightness, 50,000 hrs of backlight life 17" LCD, 280 nits brightness, 50,000 hrs of backlight life
Resolution	1024 x 768, 1280x1024, 1400 x 1050
D/C	ATI M6 chipset AGP card with 64MB Analog-to-digital conversion board
Keyboard/Mouse	108 keys, multi-languages/touchpad, RJ-45 Connector
Case Size	17.5" x 13.1" x 11.6" (445mm x 333mm x 294mm)
Power Supply	Full range PS/2 400 Watt with Active PFC
SKD Weight	12.2 kgs (27.0 lbs)
Speaker	Built-in amplified speaker Amplified board output: 2 x 6 Watt Stereo Dual Speaker output: 2 Watt
Carrying Case	Padded carrying case with wheels
Card Stabilize Bars	2
Cooling System	1 x 60mm x 60mm x 15mm (chassis fan) 2 x 40mm x 40mm x 20mm (chassis fan) 1 x 80mm x 80mm x 15mm (air duct)
Case	External chassis-flame retardant ABS plastic/internal chassis-gold color aluminum alloy

Environmental Specification

Oper. Temp.	0°C-50°C
Relative Lum.	20-80% (non-condensing)
Shock (operating, all axes)	15g
Vibration (operating, all axes)	1.25g @ 10-100Hz
Comply to	CE & FCC Class B, CCC