



## General Purpose Bells

### AC and DC Models


### 156G Series

#### FEATURES

- > 3", 4" and 6" gong sizes
- > Low current drain permits long wire runs
- > Supplied with weatherproof gasket for outdoor applications
- > Corrosion resistant gray finish

Self-contained underdome monitor bell. Weatherproof, insulated, and grounded vibrating bell with concealed plunger. Mounts on 3 3/4" (95mm) bolt circle.

For low cost, light duty installations in factories, institutions, offices, and OEMs. Uses include doorbells, extension signals, warning bells and annunciation. Suitable for AC systems with battery backup.



Cat No.	Size	Volts	Amps	dB at 1m / 10 ft.	Dimension	
					A	B
156G-3AM 156G-3AX 156G-3G1 156G-3G5	3" (76 mm)	6-8V DC 8-10V AC 12-18V DC 24V DC 24V AC	0.80 0.20 0.15 0.30	78 / 72	3" (76mm)	1 7/8" (48mm)
156G-4AM 156G-4G1 156G-4G5	4" (102 mm)	6-8V DC 8-10V AC 24V DC 24V AC	0.80 0.15 0.30	82 / 76	4" (102mm)	1 7/8" (48mm)
156G-6AM 156G-6AW 156G-6G1 156G-6G5	6" (152 mm)	6-8V DC 8-10V AC 20-24V DC 24V DC 24V AC	0.80 0.15 0.15 0.30	86 / 80	6" (152mm)	2 5/16" (59mm)

D-04