



ITM	TERM	MATERIAL	QTY	COLOR	PLATING	REMARK
1	PLASTIC HOUSING	PBT	1	BLACK		UL94V-0
2	PLASTIC COVER	PBT	1	BLACK		UL94V-0
3	CONTACT	PBS	6		GOLD FLASH AT CONTACT TIN SOLDERING AT LEAD	20T
4	FRONT SHIELD	BRASS	1		TIN (100u" MIN.)	30T
5	BACK SHIELD	BRASS	1		TIN (100u" MIN.)	30T

SPECIFICATIONS:
 RATING: 12VDC@1A
 CONTACT RESISTANCE:
 50MOHMS MAX.
 INSULATION RESISTANCE:
 100MOHMS MIN. @ 500VDC MAX.
 WITHSTAND VOLTAGE:
 500VAC/RMS @ 50~60HZ
 FOR 1 MINUTE.
 LIFE: 5,000 CYCLES.

cui inc
 9615 SW Allen, Suite 103
 Beaverton, OR 97005
 Phone: (503) 643-4899
 800-275-4899
 Fax: (503) 643-6129
 Website: www.cui.com

TITLE: Mini-Din Receptacle, Slim Type, R/A PCB MT Full Shld 6P
 PART NO. MD-60ST UNITS: Millimeters
 DRAWN BY: TODD R. WHITE APPROVED BY: SCALE: 3X
 PC FILE NAME: md-60st.dwg COPYRIGHT 2002 BY CUI INC