

Expandable Portable Computing Solution HT II-763



HTII-763

- ✓ **Enormous capacity, speedy engine**
- ✓ **Expandable and flexible removable drives**
- ✓ **Super Brilliant TFT LCD screen**

The new HTII-763, is the unpredictably powerful choice for workstation or server. A combination of five 5.25" drives and one 3.5" drive embedded in HTII-763, reveals the significance of having a creditable portable solution. Its 7-slot design is capable to accommodate any ATX size motherboards. A selection of 14", 15", or 17" super brilliant TFT LCD screen designed with an adjustable angle, allows users to fully enjoy the beauty of true colors. The new RJ-45 cabling style fits in users' "pack-and-go" modern life style, in order to avoid unnecessary detachment of cable from the computer unit. An arch design of the handle and the fine-texture coating of flash gray also draw HTII-763 a perfect appearance.

Host Applications:

- Forensics and Law Enforcement
- Field Data Acquisition
- Multimedia Applications
- Field Audits
- Troubleshooting Equipment



www.acmeportable.com
info@acmeportable.com

HT II-763 Specification

Model No.	HTII-763
Motherboard	ATX
Slot	7
Drive Bay	5 x 5.25"(open) 1 x 3.5"(open)
Color	Flash Gray
LCD	14.1", 15.1", 15.4" (Tilttable), 17" (None Tilttable) 14.1"--15.4" LCD, up to 350 nits brightness, 50,000 hrs of backlight life 17" LCD, 280 nits brightness, 50,000 hrs of backlight life
Resolution	1024 x 768, 1280x1024, 1400 x 1050
D/C	ATI M6 chipset AGP card with 64MB Analog-to-digital conversion board
Keyboard/Mouse	108 keys, multi-languages/touchpad, RJ-45 Connector
Case Size	17.5" x 13.1" x 11.6" (445mm x 333mm x 294mm)
Power Supply	Full range PS/2 400 Watt with Active PFC
SKD Weight	12.2 kgs (27.0 lbs)
Speaker	Built-in amplified speaker Amplified board output: 2 x 6 Watt Stereo Dual Speaker output: 2 Watt
Carrying Case	Padded carrying case with wheels
Card Stabilize Bars	2
Cooling System	1 x 60mm x 60mm x 15mm (chassis fan) 2 x 40mm x 40mm x 20mm (chassis fan) 1 x 80mm x 80mm x 15mm (air duct)
Case	External chassis-flame retardant ABS plastic/internal chassis-gold color aluminum alloy

Environmental Specification

Oper. Temp.	0°C-50°C
Relative Lum.	20-80% (non-condensing)
Shock (operating, all axes)	15g
Vibration (operating, all axes)	1.25g @ 10-100Hz
Comply to	CE & FCC Class B, CCC