# Matrox Graphics product line-up

Graphics solutions for professionals



## Graphics cards (add-in boards)

Matrox multi-display graphics cards offer the most comprehensive feature set with consistent stability and reliability for displaying critical information.



Product	Part #	Max. # of computer monitors			Card type	Graphics	Form factor	Monitor	Maximum reso	lutions (per display)	Card/Unit size	Extra	Extra	Matrox	
				og Total		memory	(card / bracket)	connectors	Digital	Analog	(inches / centimetres)	hardware included	features included	upgrades	(USD)
Parhelia Series - Most powerful D	DualHead/TripleHead grap	hics ca	ards												
Parhelia 128MB	PH-A8X128F	2	3	3	AGP 8x	128 MB	ATX / ATX	DVI x 2	1920 x 1200‡	2048 x 1536 (x1, x2), 1280 x 1024 (x3‡)	6.9 x 4.3 / 17.5 x 10.8	a, b, c	l, m, o	_	\$399
Parhelia 256MB	PH-A8X256F	2	3	3	AGP 8x	256 MB	ATX / ATX	DVI x 2	1920 x 1200‡	2048 x 1536 (x1, x2), 1280 x 1024 (x3‡)	6.9 x 4.3 / 17.5 x 10.0	a, b, c, d, e	l, m, o	_	\$639
Parhelia PCI 256MB	PH-P256F	2	3	3	PCI, 64-bit, 66 MHz	256 MB	ATX / ATX	DVI x 2	1920 x 1200‡	2048 x 1536 (x1, x2), 1280 x 1024 (x3‡)	7.5 x 4.2 / 19.1 x 10.7	a, b, c, d, e	l, m, o	А	\$699
Parhelia DL256 PCI	PH-P256DLF	1	1	2	PCI, 64-bit, 66 MHz	256 MB	ATX / ATX	DVI x 2	2560 x 1600 <sup>2</sup>	2048 x 1536	7.5 x 4.2 / 19.1 x 10.7	a, c, d, e	l, m	_	\$699
Parhelia APVe	PH-E128APVF	2	3	3	PCle ×16	128 MB	ATX / ATX	DVI x 2	1920 × 1200	2048 × 1536 (×1), 1920 × 1440 (×2), 1280 × 1024 (×3 <sup>‡</sup> )	6.4 × 4.4 / 16.3 × 11.1	a, b, c, j, k	l, m	G	\$349
Millennium P-Series - Comprehe	ensive series of high-resol	lution E	DualHea	d graphics	cards for all form factors ar	d bus types									
Millennium P650 PCIe 128	P65-MDDE128F	2	2	2	PCle x16	128 MB	ATX / ATX	DVI x 2	1920 x 1200	2048 x 1536 (x1), 1920 x 1440 (x2)	6.4 x 4.4 / 16.3 x 11.1	a x 2	l, m, o	В	\$249
Millennium P650 LP PCIe 64	P65-MDDE64LPF	2	2	2	PCle x16	64 MB	LP / LP	LFH60	1920 x 1200	2048 x 1536 (x1), 1920 x 1440 (x2)	5.8 x 2.7 / 14.7 x 6.9	a x 2, f, h	l, m	B, E	\$279
Millennium P650	P65-MDDA8X64F	2	2	2	AGP 8x	64 MB	ATX / ATX	DVI x 2	1920 x 1200	2048 x 1536 (x1), 1920 x 1440 (x2)	5.9 x 4.1 / 15.0 x 10.3	a x 2	l, m, o	B, C	\$169
Millennium P650 Low-profile PCI	P65-MDDAP64F	2	2	2	PCI, 32-bit, 66 MHz	64 MB	LP/ ATX	LFH60	1920 x 1200	2048 x 1536 (x1), 1920 x 1440 (x2)	5.2 x 2.5 / 13.2 x 6.4	a x 2, f, h	l, m	B, E	\$279
Millennium P750	P75-MDDA8X64F	2	3	3	AGP 8x	64 MB	ATX / ATX	DVI x 2	1920 x 1200	2048 x 1536 (x1), 1920 x 1440 (x2), 1280 x 1024 (x3‡)	5.9 x 4.1 / 15.0 x 10.3	a, b, c	l, m, o	_	\$235
QID Series - Comprehensive series	s of quad-display graphics	s cards	for all	orm factors	and bus types										
QID	QID-QDA8X128F	4	4	4	AGP 8x	128 MB	ATX / ATX	LFH60 x 2	1600 x 1200'	1600 x 1200‡	6.5 x 4.3 / 16.5 x 10.8	a x 4, f x 2	m, n	D, E	\$599
QID Pro	QID-P256PROF	4	4	4	PCI, 64-bit, 66 MHz	256 MB	ATX / ATX	LFH60 x 2	1600 x 1200‡	1600 x 1200‡	7.5 x 4.2 / 19.1 x 10.7	a x 4, f x 2	l, m, n	D, E	\$999
QID LP PCIe	QID-E128LPAF	4	4	4	PCle x16	128 MB	LP / ATX	KX20	1600 x 1200 <sup>1</sup>	1600 x 1200'	6.6 x 2.7 / 16.8 x 6.9	a x 4, g, h	m, n	н	\$799
QID Low-profile PCI	QID-P128LPAF	4	4	4	PCI, 32-bit, 66 MHz	128 MB	LP / ATX	KX20	1600 x 1200 <sup>1</sup>	1600 x 1200'	6.6 x 2.5 / 16.8 x 6.6	a x 4, g, h	m, n	н	\$799
MMS - Multi-chip dual- and quad-dis	splay graphics cards enab	oling ad	lvanced	multi-moni	or configurations										
G450x2 MMS	G45X2DUAL-BF	2	2	2	PCI, 32-bit, 66 MHz	64 MB	ATX / ATX	LFH60	1280 x 1024	2048 x 1536	6.5 x 4.2 / 16.5 x 10.7	a x 2, f	m, n	D, E	\$559
G450x4 MMS	G45X4QUAD-BF	4	4	4	PCI, 32-bit, 66 MHz	128 MB	ATX / ATX	LFH60 x 2	1280 x 1024	2048 x 1536	6.5 x 4.2 / 16.5 x 10.7	a x 4, f x 2	m, n	D, E	\$699
Millennium G-Series - Cost-effe	ctive and highly flexible D	ualHea	ıd grapl	nics cards fo	r all form factors and bus t	ypes including PC	I Express x1								
Millennium G550 PCIe	G55-MDDE32F	2	2	2	PCle x1	32 MB	ATX / ATX	DVI x 2	1280 x 1024 <sup>‡</sup>	2048 x 1536 (main), 1600 x 1200 (secondary)	4.4 x 3.6 / 11.1 x 9.1	a x 2	n	В	\$139
Millennium G550 LP PCIe	G55-MDDE32LPDF	2	2	2	PCle x1	32 MB	LP / LP	LFH60	1280 x 1024 <sup>‡</sup>	2048 x 1536 (main), 1600 x 1200 (secondary)	6.4 x 2.7 / 16.3 x 6.9	a x 2, f, h	n	B, E	\$169
Millennium G550	G55+MDHA32DRF	1	2	2	AGP 4x	32 MB	ATX / ATX	DVI, HD15	1280 x 1024	2048 x 1536 (main), 1600 x 1200 (secondary)	6.6 x 3.2 / 16.8 x 8.1	a, c	n	_	\$125
Millennium G550 Low-profile PCI	G55MDDAP32DBF	2	2	2	PCI, 32 bit, 66 MHz	32 MB	LP / ATX	LFH60	1280 x 1024 <sup>‡</sup>	2048 x 1536 (main), 1600 x 1200 (secondary)	6.6 x 2.5 / 16.8 x 6.5	h, i	n	B, E, F	\$149
Millennium G550 Dual DVI	G55MADDA32DBF	2	2	2	AGP 4x	32 MB	LP / ATX	LFH60	1280 x 1024‡	2048 x 1536 (main), 1600 x 1200 (secondary)	6.6 x 2.5 / 16.8 x 6.5	h, i	n	B, E, F	\$150
Millennium G450 PCI	G45FMDVP32DBF	1	2	2	PCI, 32 bit, 33 MHz	32 MB	ATX / ATX	DVI, HD15	1280 x 1024	2048 x 1536 (main), 1600 x 1200 (secondary)	5.9 x 4.0 / 15.0 x 10.1	a	n	В	\$115
Millennium G450 Low-profile	G45FMLDVA32DBF	1	2	2	AGP 4x	32 MB	LP / LP	DVI	1280 x 1024	2048 x 1536 (main), 1600 x 1200 (secondary)	6.6 x 2.5 / 16.8 x 6.5	b, h	n	В	\$145
Millennium G450	G45FMDHA32DBF	_	2	2	AGP 4x	32 MB	ATX / ATX	HD15 x 2	_	2048 x 1536 (main), 1600 x 1200 (secondary)	5.9 x 3.3 / 15.0 x 8.3	_	n	В	\$95
Epica Series - Dual- and quad-dis	play graphics cards for thi	in clien	nts												
Epica TC4	EPI-TC4P128LPAF	4	4	4	PCI, 32 bit, 33 MHz	128 MB	LP / ATX	KX20	1600 x 1200 <sup>1</sup>	1600 x 1200'	6.6 x 2.5 / 16.8 x 6.4	a x 4, g, h	m, n, p	_	\$849
Epica TC2	EPI-TC2P64LPAF	2		2	PCI, 32 bit, 33 MHz	64 MB	LP / ATX	LFH60	1920 x 1200	2048 x 1536 (x1), 1920 x 1440 (x2)	5.2 x 2.5 / 13.2 x 6.4	a x 2, f, h	m, p	B, E	\$309
Epica TC2-Lite	EPI-TC2P32LPAF	2		2	PCI, 32 bit, 33 MHz	32 MB	LP / ATX	LFH60	1280 x 1024 <sup>‡</sup>	2048 x 1536 (main), 1600 x 1200 (secondary)	6.6 x 2.5 / 16.8 x 6.4	a x 2, f, h	n, p	B, E	\$199

Extra hardware	i LFH60-to-HD15 dual-monitor adapter cable (1-foot)	Matrox upgrades	Part #	Notes		
a DVI-to-HD15 connector adapter	j DVI-to-HD15/DVI dual-monitor adapter cable (1-foot)	A Video input adapter cable (composite video and S-video, 1-foot)	CAB-DVI-VINF CAB-HD15-TVF P65-UPGRADE-KIT CAB-L60-2XTVF CAB-L60-2XD6F	<ul> <li>Card size = length (not including bracket and bracket connectors) x height (including slot connector)</li> <li>PCle x16 cards aren't downward compatible with PCle slots designed for bandwidths (e.g., x1, x4, x8).</li> <li>PCle x1 cards are compatible with compliant PCle slots (e.g., x1, x4, x8, x</li> </ul>		
b DVI-to-HD15 dual-monitor adapter cable (1-foot)	k HD15-to-component-video (HDTV) adapter cable (1-foot)	B TV-output adapter cable (composite video and S-video, 1-foot)				
c TV-output adapter cable (HD15 to composite video and S-video, 1-foot)	Extra features	C Millennium P650 TripleHead™ upgrade kit				
d Stereo-3D bracket for secondary slot (mini DIN3 connector)	OpenGL® acceleration	Dual TV output adapter (composite video and S-video, 1-foot)     E LFH60-to-DVI dual-monitor cable (6-foot)		Matrox PCI cards are compatible with all PCI and PCI-X slots (not PCIe slo     For LP (Low-Profile) cards with ATX brackets, cards with factory-installed L		
e Stereo-3D adapter cable (mini DIN3 connector, 1-foot)	m Pivot (display rotation) support					
f LFH60-to-DVI dual-monitor adapter cable (1-foot)	n Support for displays with special aspect ratios	F LFH60-to-DVI dual-monitor adapter cable (1-foot)	CAB-L60-2XDF	<ul> <li>be available.</li> <li>With special monitor settings, Matrox products may support higher digital r</li> </ul>		
g KX20-to-DVI quad-monitor adapter cable (1-foot)	Matrox-certified with leading CAD and/or GIS software	G DIN8-to-composite video input adapter cable (1-foot)	CAB-DIN8-CVINF	those listed here.		
h Extra bracket for different form factor (LP or ATX)	Passive cooling, low-wattage, client-server software support	H Quad TV output adapter cable (composite video and S-video, 1-foot)	CAB-KX20-QTVF			

‡ The resolution of each display must be the same. 1 Support for pairs of independent resolutions. 2 Dual Link DVI.

or different

• Matrox products support the analog resolutions listed here at 60 Hz or higher.

 All products above are RoHS-compliant. For more information, see: www.matrox.com/environment

, x16). slots). d LP brackets may

al resolutions than

## Matrox multi-display software features

**Customizable Unattended Install** • Enables large corporate installs to create a standard set of desktop features and settings that can be implemented site-wide with a one-click install

Matrox NT-Style Stretched Desktop • Enables the desktop to be setup as one single

• Multiple screen setup for viewing in landscape

• In independent mode, permits rotation of all

Stretched Desktop set of displays 90 or 270

• Permits single rotation of an NT-Style or

large desktop in Win® 2K and Win® XP instead of four independent ones



#### Matrox PowerSpace

- Create multiple virtual desktops to accommodate applications running simultaneously
- Use hot keys to navigate between each virtual desktop to see a completely different set of applications
- Save and recall application positions
- Save and migrate settings to other systems

## Matrox Multi-Clone

 Enables you to display the same desktop across all displays

## **Independent Desktop**

• Enables the set up of 3 or 4 independent desktops at the same resolution





## Matrox Desktop Divider

• Enables users to divide a single desktop into smaller display units for better organization of space

### Matrox PowerRes

- Enables EDID override and the use of a wide variety of specialty widescreen 16:9 & 16:10 and 4:3 & 5:4 resolutions and timings
- · Enables the ability to add custom resolutions



## Matrox PowerDesk

displays 90 or 270 degrees

Matrox Pivot

or portrait mode

dearees

· Matrox desktop management suite provides the user with controls for managing the behavior of how and where windows are opened, even while using NT-Style Stretched Desktop.

For more information on which products or drivers support these features, please contact Matrox.

## Matrox EpicA software for thin computing

Matrox PowerDesk Epica and Matrox PowerSpace Epica software suites are installed on the server side to enhance the user experience with multidisplay remotely hosted desktops. The two innovative desktop management tools have been exclusively designed for the Matrox Epica series of graphics cards (Epica TC2-Lite, Epica TC2 and Epica TC4), to provide a hardware and software solution that offers powerful productivity-enhancing features and tools for thin-computing environments.

#### PowerDesk EpicA key features:

- Multi-monitor awareness capability
- Resolution auto-detection
- · Maximize windows across a specified number of displays
- Control dialog box and message box positioning




A single remote session from a single client device, spanning across multiple monitors. Applications can be maximized across a specified number of displays.

Note: Multiple remote sessions from a single client device spanning across multiple monitors is also possible.

### PowerSpace EpicA key features:

- Create multiple workspaces to better organize screen space
- Define up to 9 virtual desktops per monitor, or per multi-monitor workspace, that can be labeled and toggled with hotkeys
- Save application positions per workspace
- Start applications automatically upon login and restore them to their saved locations









## Graphics eXpansion Modules (GXMs)

Matrox DualHead2Go and TripleHead2Go are easy-to-use, external Graphics eXpansion Modules that allow users to add multi-display capabilities to a notebook or desktop PC via external connectivity.





Product	Part Number Additional monitor support		Connectors	Hardware included	Max. resolution (per display)	Dimensions	Pricing
DualHead2Go Analog Edition	D2G-A2A-IF	2	HD15 x 3 (1 input, 2 outputs); USB x 1 (power)	2-foot HD15-to-HD15 (analog) monitor cable, USB power cable	Analog 1280 x 1024*	3.6" x 3.8" x 1.0" (9.2 cm x 9.5 cm x 2.5 cm)	\$169
DualHead2Go Digital Edition	D2G-A2D-IF	2	HD15 x 1 (input); DVI-I x 2 (outputs); USB x 1 (power)	2-foot HD15-to-HD15 (analog) monitor cable, USB power cable	Analog/Digital 1920 x 1200*	3.9" x 5.5" x 1.3" (10.0 cm x 14.0 cm x 3.2 cm)	\$229
TripleHead2Go Analog Edition	T2G-A3A-AJF** T2G-A3A-EUF** T2G-A3A-FEF**	2 or 3	HD15 x 4 (1 input, 3 outputs)	2-foot HD15-to-HD15 monitor cable, 2-foot DVI-to-HD15 monitor cable, external 5VDC power adapter, region-specific power cable(s)	Analog 1280 x 1024*	3.6" x 4.2" x 1.0" (9.2 cm x 10.7 cm x 2.5 cm)	\$299
TripleHead2Go Digital Edition	T2G-D3D-IF	2 or 3	HD15 x 1 (input); DVI-I x 4 (1 input, 3 outputs); USB x 1 (power)	2-foot HD15-to-HD15 monitor cable, 2-foot DVI-to-DVI monitor cable USB power cable	Analog/Digital 1280 x 1024*	3.9" x 5.5" x 1.3" (10.0 cm x 14.0 cm x 3.2 cm)	\$329

\* For notes on resolution limitations with certain graphics chips and for notes on additional resolution support, please contact Matrox. \*\* The part number for North America and Japan uses "AJ" while the part number for Europe and the rest of Asia uses "EU" or "FE", respectively.

## **Remote Graphics Units (RGUs)**

Matrox Extio series of products are the world's first fully integrated multi-display Remote Graphics Units, separating the I/O interface of the computer - the keyboard, mouse, audio peripherals and graphics hardware - from the rest of the computer by up to 820 feet (250 meters) of fiber-optic cable. Featuring a Matrox-designed graphics chip, 128 MB of memory, support for up to 4 analog or digital monitors, passive cooling (heat sink with no fan) for silent operation and extra reliability, these products save space at the user station and allow system administrators to access and maintain the system at a separate location.



Product	Part Number	Number of displays supported Memory (analog & digital)		Connectors	Max. analog & digital resolutions (per display)	Dimensions	
Extio F1400	XTO-F1400F	4	128 MB	4 DVI-I connectors <sup>1</sup> , 6 USB 2.0 ports, stereo or analog audio connectors, dual-LC fiber-optic connector, power input	1920 x 1200²	11.8" x 1.2" x 5.6" (30.0 cm x 2.9 cm x 14.2 cm)	
Extio F1420	XTO-F1420F	4	128 MB	4 DVI-I connectors', 6 USB 2.0 ports, stereo or analog audio connectors, dual-LC fiber-optic connector, power input, 2 FireWire ports	1920 x 1200²	11.8" x 1.2" x 5.6" (30.0 cm x 2.9 cm x 14.2 cm)	
Extio F1220	XTO-F1220F	2	128 MB	2 HD15 & 2 DVI-I connectors, 6 USB 2.0 ports, stereo or analog audio connectors, dual-LC fiber-optic connector, power input, 2 FireWire ports	1920 x 1200	11.8" x 1.2" x 5.6" (30.0 cm x 2.9 cm x 14.2 cm)	

4 DVI-to-HD15 connector adapters included <sup>3</sup> Earlier versions support a maximum resolution of 1600x1200. Please contact your Matrox sales representative for details if required. Note: Fiber-optic cable and Matrox interface card for either PCI (part #: XTOA-FP66LPAF) or PCIe (part #: XTOA-FELPAF) sold separately. Contact Matrox for compatibility information.

## Thin computing solutions

Matrox Epica hardware and software suite for thin computing features dual- and quad-display PCI graphics cards with low power consumption, passive (fanless) cooling and Matrox PowerDesk Epica server-based software to manage multi-display configurations in remote sessions.

For more information on Epica TC4, Epica TC2 and Epica TC2-Lite graphics cards, see "Graphics cards (add-in boards)" section, and for more information on Epica software, see "Matrox Epica software for thin computing."



## Specialized products

- Matrox Parhelia Precision SDT graphics card for digital stereoscopic displays
- Matrox Parhelia Precision SGT graphics card for stereoscopic grayscale monitors
- Matrox Parhelia HR256 graphics card for 3840 x 2400 high-pixel density monitors
- Matrox graphics cards for projection
- · Matrox air traffic control graphics controller boards

- Embedded system solutions
- Matrox PPX and VPX display wall controller capture and output boards for video walls
- Matrox AuroraVX<sup>™</sup>, MED<sup>™</sup>, RAD<sup>™</sup> and TheatreVUE<sup>™</sup> Series for Medical Imaging

## **About Matrox Graphics**

Matrox Graphics is the leading manufacturer of graphics solutions for corporate professionals and has been delivering high-quality, innovative 2D/3D and video graphics accelerators since 1976. The first to introduce multi-display technology from a single chip in 1999, Matrox Graphics combines its proven graphics chip designs, reliable software development and dependable card manufacturing expertise to produce products that are reputed worldwide for their superior image quality, practical ingenuity and unwavering stability. Matrox has recently extended its multi-display expertise to new revolutionary multi-display graphics hardware, featuring Graphics eXpansion Modules, Remote Graphics Units and thin computing solutions.

Vertically integrated and offering a full range of products that satisfy the specific real-world needs of professional users, Matrox is the leading worldwide supplier of optimized graphics solutions for segments such as:



Finance & Insurance



Editina



Medical Imaging



CAD & GIS



Dispatch, Security & Process Control



Information Displays



Specialized Applications

## **Competitive Advantages**

#### Proven technology leadership

 Responsible for bringing multi-display capabilities to the corporate environment, Matrox continues to focus on evolving customer needs with new revolutionary multi-display technologies.

### Top-to-bottom manufacturing

- Matrox is in complete control of the entire manufacturing process and complements its hardware innovation with superior driver and software development.
- Matrox products feature exceptional image quality and industry-leading MTBF (mean-time-between-failure).
- Matrox products have long product life cycles, reducing the burden on enterprise for frequent and expensive qualifications.

## Adopted by industry leaders

. Working closely with government, corporate and industrial customers has allowed Matrox to consistently innovate and introduce products with productivity-enhancing features to address specific needs in the industry.

#### Custom design services

• The Matrox specialized applications department offers fee-based design services including driver customization, customized hardware and application/feature development.

## Direct product support

 Matrox stands behind its products offering world-class pre- and post-purchase support and client service to all OEM, VAR, distributor, and end user customers.

#### For more information on Matrox products, visit www.matrox.com/graphics.

#### Americas (Headquarters) Matrox Graphics Inc.

Sales Tel: 1-800-361-1408 or 1-514-822-6366 Sales Email - North America: graphics.sales@matrox.com Sales Fmail – Latin America Info-latinamerica@matrox.com

United Kingdom Matrox UK Sales Tel: +44 (0) 1895 827264 Sales Email - UK, ROI, Benelux, France, Spain, Portugal and MEA: graphic.info.uk@matrox.com

#### Germany Matrox Electronic Systems GmbH Sales Tel: +49 (0) 89 62170-444 Sales Email - Germany, Austria, Switzerland: Info-CentralEurope@matrox.com Sales Email - Denmark, Finland, Norway, Sweden Info-NorthernEurope@matrox.com Sales Email - Eastern Europe: Info-EasternEurope@matrox.com

## Asia Pacific Matrox Asia Ltd.

Sales Email - China, Hong Kong, Taiwan: Info-China@matrox.com Sales Email - Japan: Info-Japan@matrox.com Sales Email - All other Asia-Pacific countries Info-AsiaPacific@matrox.com

Italy Ufficio Matrox per l'Italia 3G Electronics SRL Sales Tel: 02-5253095 Sales Email: vendite@treg.it



Matrox believes the information in this document is accurate and reliable, but reserves the right to make changes in specifications at any time and without notice