



# PW-330ATXE-12V

330W PS/2 power supply for Intel® Pentium® 4 processor based solution



## FEATURES

- PS/2 ATX power supply suitable for 2U, node chassis and up chassis
- ATX 2.03 standard compliant
- Best solution for entry-level Intel® Pentium® 4 processor based system
- Max. +5V standby output is 2A

## ORDERING GUIDE

- **PW-330ATXE-12V**  
330W PS/2 ATX power supply for Pentium 4 processor

## DC OUTPUT

	+5	+3.3V	+12V	-5V	-12V	+5Vsb
<b>Max. Load</b>	30A	28A	16A	0.3A	0.8A	2A
<b>Min. Load</b>	0.1A	0.3A	0A	0A	0A	0A
<b>Load Reg.</b>	±5%	±5%	±5%	±5%	±10%	±5%
<b>Ripple</b>	±1%	±1.5%	±1%	±1%	±1%	±1%
<b>Noise</b>	±1%	±1.5%	±1%	±1%	±1%	±1%

## SPECIFICATION

Input Voltage	90V ~ 132V, 180V ~ 264V AC selectable
Input Frequency	47 ~ 63 Hz
Input Current	10A@115V, 5A@230V
Efficiency	> 68%
Holdup Time	16.7 ms. at full load
Over Voltage Protection	+5V: 5.6 ~ 6.5V; +3.3V: 4.0 ~ 4.5V; +12V: 13.5 ~ 15.5V
Over Power/Load Protection	+5V, +3.3V, +12V, output power over 105% ~ 160%
MTBF	100,000 hrs
EMI & Safety Approval	UL, cUL, TUV, CE, FCC
Temperature/Humidity	Operating: 0 ~ 40°C, 10 ~ 90%RH Storage: -40 ~ 70°C, 5 ~ 95%RH
Dimension (WxDxH)	150 x 140 x 86 mm; 5.9" x 5.5" x 3.4"