

# Industrial Monitor DM & SRM Series

10.4", 12.1", 15", 17", LCD Monitor

*With the auto-dimming function, the display's brightness will automatically adjust to the light source.*

IEI's Sun Readable Monitors with enhanced ultra-high brightness TFT LCD color panels comes in three sizes and with our proprietary direct edge lighting and backlighting techniques. Our Sun Readable Monitors are available from 700 to 1750 units and comes with up to 16.7 million colors. These products are modeled to handle outdoor applications, such as KIOSK, ATMs, and car navigation systems...etc.

## Main Features

- ◆ SRM: Sun-Readable Monitor with high luminance
- ◆ Aluminum front panel is available for a harsh environment
- ◆ Plastic front panel provides a light & economical solution.
- ◆ Auto-Dimming function available with aluminum front panel for SRM Series
- ◆ Analog VGA Input



Protected against dust (no harmful deposit)



Protected against jets of water from all directions



*Aluminum Made Front Panel meets IP65 standard*

## Analog VGA Input



**DM-64T**  
6.4" TFT LCD 12VDC Input Analog VGA Input  
Optional: T-R064B 6.4" 3M resistive touch screen



**SRM-150AW**

OSD and Auto Dimming function



**DM-150AW**

OSD (On Screen Display)



**DM-84T**  
8.4" TFT LCD 12VDC Input Analog VGA Input  
Optional: T-R084B 8.4" 3M resistive touch screen



