

Expandable Portable Computing Solution HT II-767



HTII-767

Host Applications:

- Forensics and Law Enforcement
- Field Data Acquisition
- Multimedia Applications
- Field Audits
- Troubleshooting Equipment

- ✓ **Enormous capacity, speedy engine**
- ✓ **Expandable and flexible removable drives**
- ✓ **Super Brilliant TFT LCD screen**

The new HTII-767, is the unpredictably powerful choice for workstation or server. A combination of five 5.25" drives and one 3.5" drive embedded in HTII-767, reveals the significance of having a creditable portable solution. Its 7-slot design is capable to accommodate any ATX size motherboards. The 17" super brilliant TFT LCD screen designed with an adjustable angle, allows users to fully enjoy the beauty of true colors. The new RJ-45 cabling style fits in users' "pack-and-go" modern life style, in order to avoid unnecessary detachment of cable from the computer unit. An arch design of the handle and the fine-texture coating of flash gray also draw HTII-767 a perfect appearance.



www.acmeportable.com
info@acmeportable.com

HT II-767 Specification

Model No.	HTII-767
Motherboard	ATX
Slot	7
Drive Bay	5 x 5.25"(open) 1 x 3.5"(open)
Color	Flash Gray
LCD	17" (None Tiltable) 350 nits brightness, 30,000 hrs of backlight life
Resolution	1280x1024
D/C	Analog-to-digital conversion board
Keyboard/Mouse	108 keys, multi-languages/touchpad, RJ-45 Connector
Case Size	17.52" x 13.11" x 11.89" (445mm x 333mm x 302mm)
Power Supply	Full range PS/2 400 Watt with Active PFC
SKD Weight	27 pounds / 12 kg
Speaker	Built-in amplified speaker Amplified board output: 2 x 6 Watt Stereo Dual Speaker output: 2 Watt
Carrying Case	Padded carrying case with wheels
Card Stabilize Bars	2
Cooling System	1 x 60mm x 60mm x 15mm (chassis fan) 2 x 40mm x 40mm x 20mm (chassis fan) 1 x 80mm x 80mm x 15mm (air duct)
Case	External chassis-flame retardant ABS plastic Internal chassis-gold color aluminum alloy

Environmental Specification

Oper. Temp.	0°C-50°C
Relative Lum.	20% - 80% (non-condensing)
Shock (operating, all axes)	15 G
Vibration (operating, all axes)	1.25 G @ 10-100Hz
Comply to	CE & FCC Class B, CCC



GSA # GS-35F-0127M / SDB # WA000017577

1330 Mountain View Circle
Azusa, CA 91702 U. S. A.
Telephone: (626) 610-1888 ■ Fax: (626) 610-1881
www.acmeportable.com ■ info@acmeportable.com

