



Features:

- Specification compliance: ATX 2.03 & ATX12V v1.1
- Forward converter circuit
- High efficiency and reliability
- Low ripple & noise
- Short circuit protection on all outputs
- Over voltage protection
- Over power protection
- 100% hi-pot test
- 100% burn in, high temperature cycled on/off
- PFC harmonics compliance: EN61000-3-2 + A1 + A2
- EMI/RFI compliance: CE, CISPR22 & FCC part 15 class B
- Safety compliance: VDE, TUV, D, N, S, Fi, UL, C-UL & CB

Electrical Specification:

- Input frequency: 50/60Hz
- In-rush current, cold start: 80A max.
- Hold up time, full load: 16ms. typical
- Efficiency; 220-240VAC, full load: >70%
- Efficiency; 100-120VAC and full range: >65%
- Dielectric withstand, input to frame/ground: 1800VAC, 1sec.
- Dielectric withstand, input to output: 1800VAC, 1sec.
- Line regulation: +/- 1% typical
- Load regulation: +/- 5% typical
- Cross regulation: +/- 5% typical
- Ripple/noise: 1%
- MTBF, full load @ 25°C amb.: >100k hrs, will vary w/ fan type
- Active PFC, 220VAC, full load: 0.99 typical

DC Output & Features:

Model	DC outputs						Total power	Input voltage		PFC options Active	Pentium 4 connectors	AMD ⁴ recommended
	+3.3V	+5V	+12V	-5V	-12V	+5Vsb		full range	220v fixed			
SS-300FK	28A	30A	15A/18A ²	0.5A	0.8A	2A	300w	Yes	---	Yes	Yes	
	180w(40A) ¹			0.8A ³								
SS-350FK	28A	30A	17A/20A ²	0.5A	0.8A	2A	350w	Yes	---	Yes	Yes	
	180w ¹			0.8A ³								

Remarks: 1. Combined +3.3VDC & +5VDC maximum power
 2. Peak power
 3. Combined -5VDC & -12VDC maximum power
 4. Always refer to:www1.amd.com/athlon/power for latest update

SS-xxxFK Dimensions: L203.5 x W112.8 x H83.9mm



(shown: active PFC full range or fixed ac input)



specification may change without prior notice



Sea Sonic Electronics Co., Ltd.

Head office:
 8th Fl., #19 Alley 360, Sec.1, Neihu Road
 Neihu Taipei, Taiwan ROC
 tel: +886 2 2659 0338
 fax: +886 2 2659 0530
 www.seasonic.com
 sales@seasonic.com.tw

Factories:
 I. Tao Yuan, Taiwan
 II. Dong Guan, China

USA office:
 tel: +1 626 969-9966
 fax: +1 626 969-9986

Europe office:
 tel: +31 73 644 9288
 fax: +31 73 511 2217