



Ampro CoreModule™ 800

Celeron® M PCI-104 Single Board Computer

Rugged, Ultra-High Performance, RoHS-Compliant



CoreModule 800

Choose Ampro CoreModule™ 800 for...

Rugged embedded applications that need ultra-high performance in a compact module that does not violate PC/104 outline specifications.

Description

Ampro CoreModule™ 800 PCI-104 compatible SBC offers ultra low power Centrino® performance with advanced networking, high-performance graphics and all of the PC-compatible component subsystems.



- Gigabit Ethernet
- High Performance Video
- 2 RS 232/422/485 Serial ports
- 2 USB 2.0 ports
- PCI-104 without wings

For more information, pricing, and details on volume discounts, please call us at 1.800.966.5200 or +1.408.360.0200. We'll immediately connect you to your local distributor.

Don't see the product you need? Contact us at 1.800.966.5200 or +1.408.360.0200 for information about our semi-custom and custom solutions.

Get Started Today. Order a QuickStart Kit Now.

Ordering Information

MODEL	DESCRIPTION
CM3-800-L-10	1GHz 512kB Cache QuickStart Kit (R-10 SBC, 512MB RAM, Cable Kit, Software, Documentation)
CM3-800-L-08	800MHz 0kB Cache QuickStart Kit (R-08 SBC, 512MB RAM, Cable Kit, Software, Documentation)
CM3-800-R-10	1GHz ULV Celeron® M CPU, 512kB L2 Cache, PC-104, Ethernet, 2 COM
CM3-800-R-08	800MHz ULV Celeron® M CPU, 0kB L2 Cache, PC-104, Ethernet, 2 COM
CM3-800-X-01	Cable Kit
MM3-ISA-R-11	MiniModule ISA, PCI-104 to PC/104-Plus Bridge

Specifications

PROCESSORS

- Choice of
 - 1GHz Ultra Low Voltage Celeron® M 373
 - 800MHz Ultra Low Voltage Celeron® M
- Cache – 512kB or 0kB Level 2
- Chipset – Intel 855GME/ICH4M
- FSB – 400MHz
- System Controllers – PC-compatible DMA and interrupt controllers and timers
- RealTime Clock – Battery-backed RTC/CMOS
- Watchdog timer
- Powerfail Reset – Triggers when input voltage drops below predetermined thresholds

MEMORY

- DRAM – Up to 1GB PC2700 DDR333 SODIMM

BUS INTERFACE

- PCI-104 (PCI)
- PCI-104 to PC/104-Plus bridge through optional MiniModule™ ISA card

I/O

- EIDE – Single PCI-bus Enhanced Ultra DMA 33/66/100 Synchronous IDE Interface supports up to two hard drives
- Serial – 2 ports, both are RS232/422/485
- Parallel – EPP/ECP bidirectional port
- Floppy – Supports 1 or 2 drives, shared with parallel
- USB – 2 USB 2.0 ports (two root hubs)
- Keyboard/Mouse – PS/2 interface

NETWORK INTERFACE

- Ethernet – Intel 82541 (1000BaseT) Ethernet

VIDEO INTERFACE

- Controller – Integrated Intel Extreme Graphics 2
 - AGP 4X 128-bit 3D engine
 - Supports resolutions to 2048x1536
 - Up to 64MB UMA Frame Buffer
 - Dual channel LVDS
 - Supports 3.3V or 5V flat panels

SOFTWARE & DEVELOPMENT TOOLS

- OS Support – Linux® FC6, VxWorks® v5.5.1, QNX® v6.3, Windows® CE 5.0, XP, XPe (See Web site for details)
- BIOS – AMI

MECHANICAL

- Size – 90x96mm (3.6x3.8"); PCI-104 form factor
- Power Requirements – (with 512MB RAM, 100% Loaded)
 - 1GHz 2.8A @5V
 - 800MHz 2.6A @5V
- Temperature – (100 CFM system air flow)*
 - Standard: –20° to +70°C
 - Extended: –40° to +85°C (1GHz only)
 - Storage: –55° to +85°C
- See manual for thermal operating requirements
- Board Thickness – .120" (3.05mm)

* As measured with Ampro Heatsink Kit and 100 CFM or adequate thermal solution



2515 Hellyer Ave., Ste. 110, San Jose, CA 95138 Tel. 408.360.0200 Fax 408.360.0222 sales@ampro.com

JAN.07

NOTICE: The product specifications provided in this datasheet are subject to change without notice. Every effort has been made to ensure the accuracy of this document. Ampro Computers, Inc., makes no warranties, expressed or implied, regarding errors or admissions and assumes no legal liability or responsibility for loss or damage resulting from the use of this document's information. ©2007 Ampro Computers, Inc. All rights reserved. Ampro is a registered trademark and CoreModule, LittleBoard, Little Board, ReadyBoard, ReadyBox, ReadySystem, RuffSystem, MightyBoard and MightySystem are trademarks of Ampro Computers, Inc. All other trademarks and registered trademarks are the property of their respective owners.

www.ampro.com