

VTC2047

12.1" TFT LCD 10-Slot Industrial Workstation

Analog VGA Input



OSD (On Screen Display)



SPECIFICATIONS

- ◆ 19" Rackmount, 7U height industrial workstation
- ◆ DM-121 12.1" LCD Module
 - Resolution : 800 x 600
 - Colors : 262K (18 bits colors)
 - Brightness : 250cd/m²
 - LCD MTBF : 50,000 hours
 - Backlight MTBF : 25,000 hours
 - Interface : Analog VGA input with OSD(ON Screen Display function)
- ◆ Membrane Keypad :
 - Keypad : 59 keys include 10 function keys
- ◆ Front door protected area :
 - 1 x 3.5" FDD
 - 1 x 5.25" CD-ROM
 - System power switch
 - One USB port
- ◆ Drive Bays :
 - 1 x 3.5" FDD
 - 1 x 5.25" CD-ROM
 - 1 x 3.5" HDD
- ◆ Built-in PS/2 interface touch pad on front panel
- ◆ One 12cm ball bearing cooling fan with filter
- ◆ Designed with an anti-vibration card clamp that keeps the system stable
- ◆ Optional Backplane :
 - VTC206/ VTC207, VTC237/ VTC247, VTC262, VTC225/ VTC226, VTC7476, VTC12119, VTC703 300W**
 - ATX power supply with PFC function
- ◆ Optional power supply: PS/2 size AT/ATX PSU
- ◆ Optional 3M resistive type touch screen with RS-232 interface
- ◆ Operating temperature : 0°~ 50°C
- ◆ Relative Humidity : 5 ~ 85%, non-condensing
- ◆ Vibration:
 - 5~17Hz, 0.1" double amplitude displacement
 - 17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock :10G acceleration peak to peak (11ms)
- ◆ Colors : White (PANTONE 413C)
- ◆ Dimension : 483(W) x 310(H) x 266(D)mm
- ◆ Net/GW: 14/18 (kg)

ORDERING INFORMATION

● VTC290772

7U 10 slot 12.1" TFT LCD workstation with 300W ATX with PFC power supply

Option: 3M Micro Touch Resistive touch screen

VTC2046

5U Height 14-Slot Industrial PC Chassis

Analog VGA Input



OSD (ON Screen Display) Control Key



- ◆ Supports ATX form factor PC motherboard
- ◆ Optional Backplane :
 - VTC251, VTC250, VTC244, VTC700, VTC258, VTC261, VTC229, VTC701, VTC209/2966/210/211, VTC246, VTC228, VTC233, VTC2961, VTC4370, VTC2959, VTC2958, VTC2957**
- ◆ Supports power supply :
 - PS/2 size AT/ATX power supply
 - VTC009** redundant power supply
- ◆ Optional Slide : 24" or 18"
- ◆ Vibration: 5 ~17Hz, 0.1" double amplitude displacement
17 ~ 640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : White (PANTONE 413C)
- ◆ Dimension : 431(W) x 220(H) x 470(D)mm;(17"x8.7"x18.5")
- ◆ Net/GW: 15/18 (kg)

SPECIFICATIONS

- ◆ 5U height 19" Rack mounting chassis
- ◆ Front panel with lockable door to protect disk access, power on/off and reset switch
- ◆ LCD monitor module:
 - 12.1" high Brightness TFT
 - 800x600 resolution
 - Brightness : 250 cd/m²
 - LCD interface: Analog VGA Signal input
- ◆ Drive Bays :
 - 1 x 3.5" FDD
 - 1 x 5.25" CD-ROM
 - 1 x 3.5" HDD
- ◆ Two 12cm ball bearing cooling fans
- ◆ Designed with anti-vibration card clamp to keep system stable

ORDERING INFORMATION

●VTC290773

5U 14-slot rackmount chassis with 12.1" LCD and 300W ATX PS/2 power supply

●VTC290774

5U 14-slot rackmount chassis with 12.1" LCD and 300W ATX redundant power supply

● VTC290775

5U Height 14-Slot Industrial PC Chassis With 12.1 LCD Monitor with 300W ATX PS/2 industrial power supply

Option:

● VTC920

18" Rackmount slide

● VTC921

24" Rackmount slide

● VTC922

6"extender for 18" or 24" slide

● VTC10919

3M Micro Touch Resistive touch screen