

F845G/VE+

Socket 478 PICMG Card for Pentium® 4 / Celeron™ Processor with VGA / LAN

Key-point:

- > Socket 478 for Intel® Pentium® 4 / Celeron™ Processor, up to 3.06GHz
- > Intel® 845GV Chipsets, 400 / 533 MHz FSB
- > Chipset integrated VGA function
- > Support 10/100 Base-TX Ethernet
- > 4 x USB 2.0 ports
- > WatchDog Timer, Hardware monitoring function & DOC



Specifications:

- ⊙ **Processor:**
 - * Intel® Socket 478 Pentium® 4 / Celeron™ Processor
 - * Up to 3.06GHz
- ⊙ **Core Logic:**
 - * Intel® 845GV + ICH4 chipsets
- ⊙ **BIOS:**
 - * Award BIOS
- ⊙ **Front Side Bus Speed:**
 - * 400 / 533 MHz
- ⊙ **Memory:**
 - * Two 184-pins DDR DIMM
 - * Support DDR200/266 SDRAM, up to 2GB (max.)
- ⊙ **Onboard VGA Controller:**
 - * Intel® 845GV chipset integrated VGA function
- ⊙ **LAN Controller:**
 - * Intel® 82562EM, for 10 / 100 Base-TX, Support wake up on LAN
- ⊙ **Onboard IDE:**
 - * Two EIDE channels for PIO Mode, DMA Mode
 - * Supports four ATA 100/66/33 IDE devices
- ⊙ **Multi I/O:**

Onboard Winbond® 83627HF chip, Support:

 - * 1 x IrDA by 5-pin pin-header
 - * 1 x Floppy Interface
 - * 1 x SPP / EPP / ECP parallel port by pin-header
 - * COM1 is RS-232
 - * COM2: RS-232 or RS-422/485 (jumper selectable)
- ⊙ **WatchDog Timer:**
 - * 256 Levels software programmable
- ⊙ **Keyboard / Mouse Connector:**
 - * 6-pins mini DIN for PS/2 type for Keyboard & Mouse
 - * 1 x 6-pin header connector for external Keyboard & Mouse
- ⊙ **USB:**
 - * Onboard 4 x USB 2.0 ports by pin-headers (cable by optional)
- ⊙ **SSD:**
 - * DIP socket supports M-System DiskOnChip® flash disks
- ⊙ **Hardware Monitoring:**
 - * Winbond W83627HF chip, Monitoring for CPU and system temperature, voltage and fan speed
- ⊙ **Environments:**
 - * Operation temperature: 0°C to 60°C (32°F to 140°F)
 - * Storage temperature: -20°C to 80°C (-68°F to 176°F)
 - * Relative humidity: 10% to 90% (Non-Condensing)
- ⊙ **Certification:**
 - * CE, FCC Approval
- ⊙ **Form Factor:**
 - * Full Size, PICMG compliance
- ⊙ **Audio**
 - * No support
- ⊙ **PC-104 connector:**
 - * No support
- ⊙ **Dimensions (L x W):**
 - * 13.3" x 4.8" (338mm x 122mm)

*Specification is subject to change without prior notice

Ordering Information:

Model No.	Position	Support LCD	Support VGA	Support SCSI	Support LAN	Support Audio
F845G / VE+	Standard Product	---	Yes	---	Yes	---

I/O Bracket Layout

