


- 1 Motherboards
- 2 Disk-Size SBOS
- 3 CPU Modules
- 4 PC/I/Os Plus
- 5 CPU Card
- 6 Embedded Systems
- 7 Network Security Appliance

MI933



Features

- Supports AMD Sempron™ processor, 800MHz FSB
- 1x DDR2 DIMM, Max. 2GB
- AMD M690E built-in Radeon X1270 for CRT Dual DVI on board, dual view supported
- 2x Realtek PCI-E Gigabit LAN
- 2x SATA II, 2x COM, 8x USB, 1x PCI
- +12V DC In, optional LPC TPM

System

CPU	AMD Sempron™ 64-bit processor, 1.0GHz/1.5GHz
System Memory	1x DDR2 DIMM, 400MHz, Max. 2GB
System Chipset	AMD M690E + SB600, 800MHz FSB
BIOS	Award
Watchdog Timer	256 levels
SSD	N/A
H/W Monitor	Yes
Expansion Slots	1x PCI, Reserved headers for LPC TPM and 4x COM

Graphics

VGA Controller	AMD M690E integrated Radeon™ X1200 series
VGA Memory	Shared memory, Max. 1024MB
Display Interface	Supports CRT, dual DVI, dual view display (CRT with DVI or dual DVI)

Ethernet

Controller	2x Realtek 8111C PCI-E Gigabit LAN
Connector	RJ-45 on board

Multi I/O

Chipset	Winbond W83627EHG 1x IDE, 1x KB, 1x mouse, 1x RS-232, 1x RS232/422/485, 2x SATA II
USB	4 ports on board Pin header for 4 ports (USB 2.0)
Audio	AMD SB600 built-in HD audio w/ Realtek ALC888 codec for 7.1CH
Others	Digital I/O (4-in/4-out), +12V DC-in

Mechanical and Environmental

Dimensions	170mm x 170mm (6.7" x 6.7")
Max. Power Requirement	AMD Sempron™ 64-bit processor, 1.0GHz w/ 2x 1GB DDR2-667 +12V: 3.22A +5V: 1.3A
Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	10%~90% (non-condensing)

Ordering Information

MI933	AMD Sempron™ 200U, 1.0GHz, M690E Mini-ITX motherboard w/ VGA and dual PCI-E Gigabit LAN
MI933-15	AMD Sempron™ 210U, 1.5GHz, M690E Mini-ITX motherboard w/ VGA and dual PCI-E Gigabit LAN
CMI201-60	Chassis for Mini-ITX (low power), w/ 60W PSU, 2.5" HDD holder
CMI201-85	Chassis for Mini-ITX (low power), w/ 85W PSU, 2.5" HDD holder
CMI203-180	Chassis for Mini-ITX, w/ 180W PSU, 3.5" HDD holder
CMI203-250	Chassis for Mini-ITX, w/ 250W PSU, 3.5" HDD holder



Remarks:
 1. For optional daughter boards and riser cards, please refer to page 19-20.
 2. Specifications are subject to change without prior notice.