

Axis High Power over Ethernet midspans & splitters

High Power over Ethernet for Axis PTZ dome network cameras.



- > Reduced installation costs
- > Support for Axis PTZ dome network cameras
- > IEEE 802.3at
- > IEEE 802.3af compliance

Axis High Power over Ethernet midspans and splitters offer an easy, fast and cost-effective solution for powering network video products — specifically PTZ dome network cameras — without the need to install power outlets and electrical cabling.

Axis High Power over Ethernet (High PoE) midspans and splitters enable Axis network video products to receive data and power over the same Ethernet cable.

The High PoE products make it easier to install network video products in areas where power cabling and outlets are unavailable, thereby reducing installation costs.


These midspans and splitters are used to power network devices that require more power, as specified by the IEEE 802.3at standard. The midspans are also IEEE 802.3af compliant, meaning that they can be used with all Axis network video products with built-in PoE support.

The function of a midspan is to inject power into a network cable. A splitter, which separates data and power coming over an Ethernet cable, is used for a network video product without built-in support for PoE.

Technical Specifications – Axis High Power over Ethernet midspans

| Midspan | |
|------------------------------------|---|
| Model | AXIS T8122 DC 30 W Midspan AXIS T8123 High PoE 30 W Midspan 1-port AXIS T8124 High PoE 60 W Midspan 1-port |
| Function | Data and power are fed to a network video product through an Ethernet cable; use together with a High PoE splitter for a network video product without built-in PoE support |
| Data rate | 10/100/1000 Mbps |
| Data Et Power | |
| Connectors | Shielded RJ-45, EIA 568A and 568B |
| Network cables | Shielded category 5 (or higher) |
| Wiring | Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over spare pairs 4/5 (+) and 7/8 (-) AXIS T8124: Power over pairs 1/2(-), 3/6(+), 4/5 (+) and 7/8 (-) |
| Output power | AXIS T8122: 52 V DC at 12–24 V DC IN (max. 30 W) 44–57 V DC at 45–57 V DC IN (max. 30 W) AXIS T8123: 55 V DC (max. 30 W) AXIS T8124: 55 V DC (max. 60 W) |
| Input power | AXIS T8122: 12 to 24 V DC (max. 40 W) or 45 to 57 V DC* (max. 35 W) AXIS T8123: AC Input Voltage: 100 to 240 V AC (max. 37 W) AC Frequency: 50 – 60 Hz AXIS T8124: AC Input Voltage: 100 to 240 V AC (max. 74 W) AC Frequency: 50 – 60 Hz |
| Installation and management | Plug-and-play installation; automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display |

AXIS T8122 DC 30 W Midspan – Maximum cable length between network switch and powered device



| General | |
|--------------------------------------|---|
| Display and indicators | Port interfaces are located on the front panel AXIS T8122: Power indicator: AC power Network indicator: Port AXIS T8123 and AXIS T8124: System indicator: AC power Channel indicator: Power For more information, see www.axis.com/techsup |
| Compliance | IEEE 802.3af, IEEE 802.3at, RoHS, WEEE, CE |
| Mounting | Wall or shelf mounting |
| Approvals | FCC Part 15, Class B with FTP cabling EN 55022 Class B (Emissions), EN 55024 (Immunity), VCCI Safety: CB, UL/cUL per EN 60950-1, GS Mark per EN 60950-1, KCC, UL-AR AXIS T8122: IEC 60068-2-6, IEC 60068-2-27 |
| Operating conditions | Humidity max. 95% RH (non-condensing) AXIS T8122: -20 °C to 65 °C (-4 °F to 149 °F) AXIS T8123: -10 °C to 55 °C (14 °F to 131 °F) AXIS T8124: -10 °C to 45 °C (14 °F to 113 °F) at 60 W -10 °C to 55 °C (14 °F to 131 °F) at 30 W -10 °C to 60 °C (14 °F to 140 °F) at 25 W or less |
| Storage | AXIS T8122: -40 °C to 74 °C (-40 °F to 165 °F) |
| Dimensions (HxWxD) and weight | AXIS T8122: 117 x 95 x 41 mm (4.6" x 3.7" x 1.6") AXIS T8123 and AXIS T8124: 51.3 x 87.9 x 166 mm (2.0" x 3.46" x 6.53") AXIS T8122: 200 g (0.4 lb.) AXIS T8123: 350 g (0.7 lb.) AXIS T8124: 400 g (0.8 lb.) |
| Included accessories | AXIS T8122: DC input terminal connectors |

*To power units compliant with IEEE 802.3at, AXIS T8122 requires 50 to 57 V DC IN; whilst to power units compliant with IEEE 802.3af, AXIS T8122 requires 45 to 57 V DC IN

More information is available at www.axis.com and on products' Installation Guide

Technical Specifications – Axis High Power over Ethernet splitters

| Splitters | |
|-----------------------|---|
| Models | AXIS T8126 High PoE Splitter 12V AXIS T8128 High PoE Splitter 24V |
| Function | Separate data and power coming over a network cable for a network video product without built-in PoE support |
| Data Et Power | |
| Connectors | Data Et power in: Shielded RJ-45 Data out: Shielded RJ-45 Power out: DC barrel connector; with '+' centered |
| Output current | AXIS T8126: 2 A at 12 V DC AXIS T8128: 1 A at 24 V DC |
| Input power | max. 30 W |
| Installation | Plug-and-play installation between midspan and camera |

| General | |
|--------------------------------------|---|
| Compliance | WEEE, CE |
| Operating conditions | 0 °C to 40 °C (32 °F to 104 °F) Humidity max. 90% RH (non-condensing) |
| Approvals | FCC Part 15 Class A FTP, Class A UTP EN55022 (CISPR 22) Class A Immunity EN55024 (CISPR 24) |
| Dimensions (HxWxD) and weight | 94 x 31 x 73 mm (3.7" x 1.12" x 2.87") 112 g (0.247 lb.) |
| Included accessories | AXIS T8126 – cable adapters for AXIS 214 PTZ, AXIS 215 PTZ, video encoders AXIS T8128 – cable adapter for AXIS 232D+, AXIS 233D For a complete list of supported products, please refer to www.axis.com/products/pol/high_poe/supported.htm |