

Features

Supports Intel® Core™2 Duo/Solo processors
Up to 1.86GHz, 533/667MHz FSB

DDR2 SO-DIMM x 1, Max. 2GB

Integrated VGA, supports CRT, LVDS

Integrated ICH7M 10/100 BaseT Ethernet

AC97, Watchdog timer, PCI to ISA

2 x SATA, 4 x USB 2.0, 4 x PCI



System

CPU :	Intel® Core™2 Duo/Core Duo/Solo, up to 1.86GHz (BGA CPU on board or Socket 478)
System Memory :	DDR2 SO-DIMM x 1, Max. 2GB
System Chipset :	Mobile Intel® 945GM Express + ICH7M, 533MHz/667MHz FSB
BIOS :	Award
Watchdog Timer :	256 levels
SSD :	DOM or CF socket on baseboard
H/W Monitor :	Yes
Expansion Slot :	ETX connector x 4 for PCI bus, USB, audio, VGA/CRT, LVDS, LAN, COM ports, LPT, IDE, PS/2 keyboard/mouse and ISA bus

Graphics

VGA Controller :	Mobile Intel® 945GM Express integrated Graphics Media Accelerator 950 (GMA 950), supports CRT/LVDS
VGA Memory :	Supports DVMT 3.0; Max. shared memory - 224MB
LCD Interface :	Supports 18-bit dual channel LVDS

Ethernet

Controller :	ICH7M integrated 10/100Mbps Ethernet
Connector :	On baseboard

Multi I/O

Chipset :	ICH7M, Winbond W83627EHF 1x IDE (UDMA33/66/100), 4x SATA, 2x COM, 1x FDD (slim FDD connector on board)
USB :	4 ports (USB 2.0) via baseboard
Audio :	ICH7M built-in audio + AC97 codec
Others :	ITE IT8888G PCI to ISA (slave only)

Mechanical & Environmental

Dimensions :	95mm x 114mm (3.7" x 4.5")
Max. Power Requirement :	TBC
Operating Temperature :	0°C~60°C (32°F~140°F)
Storage Temperature :	-20°C~80°C (-68°F~176°F)
Relative Humidity :	10%~90% (non-condensing)

Ordering Information

ET910	Mobile Intel® 945GM Express ETX (3.0) CPU Module w/ VGA and 10/100 Ethernet (RoHS compliant)
-------	--

Remarks:

* Specifications are subject to change without prior notice.