


IAC-F695




Full-Size Socket A AMD™ SBC



FEATURES

- Support AMD Duron™/Athlon™ Socket A Processor, 200/266 FSB
- VIA VT8363A/686B chipset
- Three DIMM sockets, support up to 1.5GB SDRAM
- Two PCI IDE port that support up to four IDE devices and Ultra DMA 100/66/33
- One FDD port, support up to two floppy devices
- Two COM ports

OPTIONAL

| Item |
|--|
|  USB Y cable with bracket |
| Part Number |
| 0800100100002 |

SPECIFICATION

CPU

Support AMD™ Socket A Processor

Chipset

VIA VT8363A/686B chipset

BIOS

Award® licensed BIOS

System Memory

3 x 168-pin DIMM sockets, support up to 1.5GB SDRAM

Flash Memory Disk

Reserved socket for DiskOnChip® from M-System, support up to 144 MB flash memory disk

IDE Interface

2 PCI IDE ports that support up to 4 IDE devices and Ultra DMA-33/66/100

Floppy Drive Interface

1 FDD port, support up to 2 floppy devices

Serial Port

2 COM ports, 1 x RS-232 and 1 x RS-232/422/485

Parallel Port

1 multi-mode parallel port (SPP / EPP / ECP)

Universal Serial Bus

Support 2 USB ports

IR Interface

Support 1 IrDA header

Digital I/O

4-bit digital I/O header

Keyboard Connector

5-pin header and 1x6-pin mini-DIN PS/2 keyboard connector

Mouse Connector

6-pin mini-DIN PS/2 mouse connector

RTC

Internal RTC with Li battery

Power Connector

1 ATX feature connector (for Wake on LAN)

Watchdog Timer

16-level time-out intervals

Power Consumption

+5V@13.22A (AMD™ Athlon 1.2GHz, 1.5GB SDRAM) +12V:270mA, -12V:30mA

Health Monitoring

On-board hardware monitoring function

Operating Temperature

0°C~60°C

Humidity

5% ~ 95% RH, non-condense

Dimensions

338.5 x 122 mm (13 1/4" x 4 5/8")

Net Weight

355g (0.78 pounds)