

Visualize The Value

# K Series LCD Monitors



Model	K-6mwb	K72b/K72mb	K726mwb	K92bw	K92mdwb	KS-19mws
<b>Panel Size</b>	15.6"	17"	17" Wide	19" Wide	19" Wide	19" Wide
<b>Display Area</b>	13.5" X 7.62"	13.3"x10.6"	14.6"x8.2"	16.1"x10.8"	16.1"x10.8"	16.1"x10.0"
<b>Pixel Pitch</b>	0.252mm	0.264mm	0.291mm	0.285mm	0.285mm	0.243mm
<b>Brightness</b>	250cd/m <sup>2</sup>	300cd/m <sup>2</sup>	250cd/m <sup>2</sup>	300cd/m <sup>2</sup>	300cd/m <sup>2</sup>	300cd/m <sup>2</sup>
<b>Contrast Ratio</b>	500:1	800:1	500:1	1000:1	800:1	1000:1
<b>Video Response</b>	8ms	5ms	8ms	5ms	5ms	5ms
<b>Horizontal Viewing Angle</b>	90°	160°	140°	170°	140°	170°
<b>Vertical Viewing Angle</b>	65°	160°	130°	160°	140°	160°
<b>Optimum Resolution</b>	1366x768	1280x1024	1280x720	1400x900	1440x900	1680x1050
<b>Display Colors</b>	16.7M	16.2M	16.2M	16.7M	16.7M	16.7M
<b>Horizontal Freq.</b>	31 - 48kHz	31 - 80kHz	31 - 82kHz	30 - 81kHz	31 - 80kHz	30 - 81kHz
<b>Vertical Freq.</b>	60 - 75Hz	60 - 75Hz	56 - 60Hz	56 - 75Hz	60 - 75Hz	56 - 75Hz
<b>Bandwidth</b>	85MHz	135MHz	135MHz	140MHz	140MHz	140MHz
<b>Compatibility</b>	PC, Mac	PC, Mac	PC, Mac	PC, Mac,	PC, Mac	PC, Mac
<b>Interface</b>	Analog	Analog	Analog	Analog	Analog x2 + DVI	Analog One D-Sub Input & One D-Sub Output
<b>Power Supply</b>	Integrated	Integrated	Integrated	Integrated	Integrated	Adapter
<b>Standby Consumption</b>	<2w	<2w	<2w	<2w	<2w	<2w
<b>Maximum Consumption</b>	25w	48w	48w	48w	48w	40w
<b>Physical Dimensions (WxDxH)</b>	15.4"x6.8"x11.9"	14.9"x7.5"x14.9"	16.6"x7.5"x13.9"	17.1"x8.3"x14.6"	17.1"x8.3"x14.6"	17.0"x14.0"x0.9"
<b>Packaging (WxDxH)</b>	17.2"x5.2"x15.8"	17.1"x5.5"x19.5"	18.5"x5.5"x15.7"	20.9"x5.5"x19.7"	20.9"x5.5"x19.7"	24.1"x20.3"x14.3"
<b>Net/Gross Weight</b>	5.5lbs / 8.8lbs	8.4lbs / 9.9lbs	8.4lbs/9.9lbs	10.2lbs / 11.7lbs	10.22lbs / 11.78lbs	10.12lbs / 14.3lbs
<b>Plug &amp; Play</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Auto Adjustment</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Integrated Speakers</b>	Yes	No/Yes	Yes	No	Yes	Yes
<b>Control Buttons</b>	5 keys	5 keys	5 keys	5 keys	5 keys	5 keys
<b>Tilt Angle</b>	+25° / -5°	+25° / -5°	+25° / -5°	+25° / -5°	+25° / -5°	+5° / -65°
<b>Kensington® Lock Port</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>VESA® Wall Mount Compatible</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Regulations</b>	FCC, UL/cUL, ROHS	FCC, UL/cUL, ROHS	FCC, UL/cUL, ROHS	FCC, UL/cUL, ROHS	FCC, UL/cUL, ROHS	FCC, UL/cUL, ROHS

www.kdsusa.com | 1-800-283-1311

© April, 2008 PTI Inc. All rights reserved. Information on this publication subject to change without notice. Screen images are simulated.



Visualize The Value

# K Series LCD Monitors



Model	K-2026mdwb	K-22mdwb	K-22mdwb2	K-2237mdwb	K-24mdwb	K-2626mdhwb
<b>Panel Size (in.)</b>	20" Wide	22" Wide	22" (21.6" VIS)	22" (21.6" VIS)	24" Wide	26" Wide
<b>Display Area (HxV)</b>	17.06x10.66	18.6 x 11.7	18.3 x 11.4	18.3 x 11.4	20.4 x 12.8	21.6 x 13.5
<b>Pixel Pitch (mm)</b>	0.258	0.282	0.277	0.277	0.270	0.2865
<b>Brightness</b>	300	300	300	300	400	300
<b>Contrast Ratio</b>	1000:1	1000:1	1000:1	1000:1	800:1	1000:1
<b>Video Response</b>	5ms	5ms	5ms	5ms	5ms	5ms
<b>Horizontal Viewing Angle</b>	170	170	170	170	160	170
<b>Vertical Viewing Angle</b>	160	160	160	160	160	160
<b>Optimum Resolution</b>	1680x1050	1680x1050	1680x1050	1680x1050	1920x1200	1920x1200
<b>Display Colors</b>	16.7M	16.7M	16.7M	16.7M	16.7M	16.7M
<b>Horizontal Freq. (kHz)</b>	30 - 81	31 - 80	31 - 80	31 - 80	30 - 75	30 - 81
<b>Vertical Freq. (Hz)</b>	56 - 76	56 - 76	56 - 76	56 - 76	56 - 76	40 - 63
<b>Bandwidth (MHz)</b>	140	146	146	146	166	166
<b>Compatibility</b>	PC, Mac	PC, Mac	PC, Mac	PC, Mac	PC, Mac	PC, Mac
<b>Interface</b>	Analog x2 + DVI	Analog D-Sub x 2 + DVI/HDCP	Analog D-Sub + DVI/HDCP	Analog D-Sub + DVI/HDCP	Analog D-Sub x 2 + DVI/HDCP	Analog D-Sub x 1 + DVI/HDMI/HDCP
<b>Power Supply</b>	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
<b>Standby Consumption (W)</b>	<2	<2	<2	<2	<2	<2
<b>Maximum Consumption (W)</b>	50	60	60	60	80	80
<b>Physical Dimensions (WxDxH)</b>	14.0x8.2x14.6	20.6x8.3x15.9	20.6x8.3x15.9	20.6x8.3x15.9	22.6x17.6x8.6	24.1x18.6x8.6
<b>Packaging (WxDxH) (in.)</b>	20.8x5.6x19.6	22.8x5.7x19.7	22.8x5.7x19.7	22.8x5.7x19.7	30.0x20.8x8.0	26.8x21.3x8.0
<b>Net/Gross Weight (lbs.)</b>	10.22/11.77	12.13 / 14.33	12.13 / 14.33	12.1/14.3	16.1 / 18.3	15.8 / 18.3
<b>Plug &amp; Play</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Auto Adjustment</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Integrated Speakers</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Control Buttons</b>	5 keys	5 keys	5 keys	5 keys	5 keys	5 keys
<b>Tilt Angle (degrees)</b>	+25/ -5	+25 / -5	+25 / -5	+25 / -5	+25 / -5	+25 / -5
<b>Kensington® Lock Port</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>VESA® Wall Mount Compatible</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Regulations</b>	FCC UL/cUL, ROHS	FCC UL/cUL, ROHS	FCC UL/cUL, ROHS	FCC UL/cUL, ROHS	FCC UL/cUL, ROHS	FCC UL/cUL, ROHS

www.kdsusa.com | 1-800-283-1311

© April, 2008 PTI Inc. All rights reserved. Information on this publication subject to change without notice. Screen images are simulated.

