

**Daniel Woodhead Safeway® Pin and Sleeve 60 Amp Exposition Devices**

- All devices are 4-pole 5-wire grounding type
- Rugged nylon construction is ideal for abusive environments



**Woodhead®**  
from **molex**

WESCO Part No.	Mfr.'s Model No.	Volts	Amps
<b>Pin and Sleeve Plug</b>			
786788-31504	Y560P	277/480 VAC	60
<b>Pin and Sleeve Inlet</b>			
786788-31507	Y560B	277/480 VAC	60
<b>Pin and Sleeve Connector</b>			
786788-31506	Y560C	277/480 VAC	60
<b>Pin and Sleeve Receptacle</b>			
786788-31505	Y560R	277/480 VAC	60

**Daniel Woodhead Safeway® Nylon Pin and Sleeve Devices**

- Use for temporary power systems, power disconnect for portable processing equipment, etc.
- Deadfront construction with self-adjusting split contact sleeves
- Latching mechanism prevents accidental disengagement
- External and internal strain relief
- Nickel-plated steel spring maintains constant pressure along contact surface to ensure electrical continuity and grounding
- UL® Listed and CSA Certified

**Woodhead®**  
from **molex**

WESCO Part No.	Mfr.'s Model No.	Volts	Amps
<b>3-Pole 4-Wire Plug</b>			
786788-70791	430P7	480V 3Ø	30
<b>3-Pole 4-Wire Connector</b>			
786788-70775	430C7	480V 3Ø	30
<b>4-Pole 5-Wire Receptacle</b>			
786788-72780	560R9	120/208V 3Ø	60

**Daniel Woodhead Watertite® Nylon Pin and Sleeve Plugs**

- Deadfront construction with self-adjusting split contact sleeves
- Nickel-plated steel spring maintains constant pressure along contact surface to ensure electrical continuity and grounding
- External and internal strain relief
- Latching mechanism prevents accidental disengagement
- Use for temporary power systems, power disconnect for portable processing equipment, etc.
- UL Listed and CSA Certified

**Woodhead®**  
from **molex**

WESCO Part No.	Mfr.'s Model No.	Volts	Amps
<b>4-Pole 5-Wire Receptacle</b>			
786788-70910	5100R9W	120/208V 3Ø	100

**Pass & Seymour® Safety Interlock Pin and Sleeve Receptacles**

- Provide maximum safety and protection against accidental shock
- Prohibit the making and breaking of plug and receptacle under load
- Impact-resistant thermoplastic construction
- Feature a heavy-duty switch handle and thermoplastic design
- NEMA Enclosure Type 4X, 12K



**Pass & Seymour**

**legrand®**

WESCO Part No.	Mfr.'s Model No.	Volts	Amps	Hubs
<b>3-Pole 4-Wire Interlocking Receptacles</b>				
785007-42048	PS430MIR7-W	480V 3Ø	30	(1) Top-Feed
785007-42057	PS460MIR5-W	600V 3Ø	60	(1) Top-Feed
785007-42058	PS460MIR7-W	480V 3Ø	60	(1) Top-Feed

**Pass & Seymour® Watertight Pin and Sleeve Devices**

- Hinged cord grip for durable performance and ease of installation
- Locking ring and cover have an integral neoprene gasket that provides a watertight seal
- Nickel-plated brass pins provide extra corrosion resistance
- Rugged nylon construction
- Rubber grommets provide watertight protection at cable entry point
- IP67 Suitability
- UL Listed and CSA Certified



**Pass & Seymour**

**legrand®**

WESCO Part No.	Mfr.'s Model No.	Volts	Amps
<b>2-Pole 3-Wire Plug</b>			
785007-84005	PS360P6-W	250 VAC/250 VDC	60
<b>3-Pole 4-Wire Plug (Thermoplastic)</b>			
785007-43046	PS430P7-W	480V 3Ø	30
<b>3-Pole 4-Wire Plug</b>			
785007-61701	PS460P12-W	125/250 VAC	60
<b>4-Pole 5-Wire Plug</b>			
785007-46046	PS460P7-W	480V 3Ø	60
<b>2-Pole 3-Wire Connector</b>			
785007-84006	PS360C6-W	250 VAC/250 VDC	60
<b>3-Pole 4-Wire Connector</b>			
785007-43045	PS430C7-W	480V 3Ø	30
785007-46045	PS460C7-W	480V 3Ø	60
785007-61702	PS460C12-W	125/250 VAC	60
<b>2 Pole, 3 Wire Receptacle</b>			
785007-84004	PS360R6-W	250 VAC/250 VDC	60
<b>3-Pole 4-Wire Receptacle</b>			
785007-43047	PS430R7-W	480V 3Ø	30
785007-61700	PS460R12-W	125/250 VAC	60
785007-46047	PS460R7-W	480V 3Ø	60

Wiring Devices

