Compact 386SX PC/104 EPC with SSD and 2MB DRAM

AR-B9612



F	eatures
•	80386SX-33MHz CPU
ϕ	PC/104 extension Bus
ϕ	Onboard 2MB DRAM
ϕ	Supports two serial ports
ϕ	Supports up to 1.5MB Flash disk
ϕ	AMI Flash BIOS
ϕ	Built-in status LED indicator
ϕ	Single 5V power requirement
ϕ	Multi-layer PCB for noise reduction

Programmable watchdog timer

Specifications

General CPU 33 MHz CPU Chipset ALI M6117C A1F **Bus Interface** PC/104 Bus Memory Onboard 1MB or 2MB DRAM (Optional) Serial Port Supports two full RS-232C serial ports or two RS-485 serial ports Solid State Disk Up to 1.5MB flash disk (3 sockets) Keyboard & Mouse PC/AT compatible keyboard Speaker External speaker with 2 pin header BIOS AMI Flash BIOS Watchdog Timer Programmable watchdog timer RTC BQ3287MT or compatible chips LED Indicator **Build-in Power LED indicator** Bus Speed 7.159MHz DMA Channels 7 DMA channels Humidity 0 to 95% (non-condensing) Interrupt Levels 15 vectored interrupt levels Power Connector 4-pin (2.5mm) power connector (+5V, GND, GND, +12V) Storage Temp. -25 to 85 degree. Power Req. +5V, 0.8A maximum PC Board 4 layers Dimensions 90.2 mm x 95.9 mm

Ordering information:

Model No.	Description	Accessories
AR-B9612	Compact 386SX PC/104 EPC with SSD and 2MB DRAM	Cable: D-SUB COM Port Cable, Keyboard Cable, Power Cable