



# PCI-40A

## Four Slot IndustryPack® Carrier for PCI

### Features

- Four IndustryPack slots on a full-length PCI slot board
- I/O via four 50-pin keyed, shrouded ribbon cable headers
- Switchable 8/32 MHz IndustryPack bus
- LEDs for CPU access and power monitor
- Filtered power rails and re-settable fuses
- Interrupt acknowledge space for retrieving IndustryPack vectors
- Reduced memory-map version available by special order



**PCI-40A** is an IndustryPack® carrier board that provides four IndustryPack slots on a single desktop or industrial PCI slot card. The IndustryPack bus clock is software-selectable on a per-slot basis between 8 and 32 MHz.

The standard 8 MB memory space is available for each IndustryPack site. High-speed 32-bit PCI host address space permits desirable linear mapping and fixed address partitions of memory, I/O and ID spaces for each IndustryPack module.

The PCI-40A uses a PLX PCI9080 controller as the PCI bus interface chip and Altera FPGA logic, which provides fully configurable PCI interrupt vector space. The PCI bus interface supports 5.0 V signaling.

Each IndustryPack site has an adjacent 50-pin I/O connector for exiting the host system through the PCI slot panel. One connector is accessible via the rear-panel. The standard connector permits most of SBS Technologies transition modules and terminal blocks to be used.

The PCI-40A meets the PCI specification and conforms to the VITA-4 IndustryPack Logic Interface Specification. This guarantees compatibility with a wide range of IndustryPacks.

The PCI-40A targets embedded computing applications in industrial automation, communications, transportation and COTS.



# PCI-40A

## Specifications

### Specifications

#### Form Factor

- PCI full-length slot

#### PCI

- PCI Specification, Rev 2.1

#### PCI Controller

- PLX 9080

#### Carrier Board Memory Space

- 64 MB\*

#### PCI Bus Interrupts Generated

- INTA# only

#### Indicators

- One green LED per IndustryPack slot for CPU access
- One red LED per rail for power monitor

#### Power Requirements

- +5V VDC, 250 mA typical
- +12 V DC, 10 mA typical
- -12 V DC, 10mA typical
- Extra power required for IndustryPack modules

#### Temperature

- Operating: 0° to 70°C
- Storage: -40° to +85°C

#### Humidity

- 5% to 95% non-condensing

#### Weight

- 0.21 kg (0.5 lb)

#### Dimensions

- 4.2" x 12.2"  
(106.7 mm x 309.9 mm)

#### Number of IndustryPack Slots

- Four
- Supports up to two double-wide IndustryPacks

#### IndustryPack Bus Clock

- Switchable 8/32 MHz per IndustryPack slot

#### IndustryPack Features Supported

- I/O space
- ID space
- Memory space
- Interrupt acknowledge cycles

#### IndustryPack Memory Size

- 8 MB per IndustryPack\*

#### IndustryPack Interrupts Supported

- Int0 and Int1 for each slot

#### I/O Access

- One 50-pin 0.1" ribbon cable header per IndustryPack slot
- One connector is rear-panel accessible

#### Fuses

- 1.5 A for 5 VDC each slot
- 1.5 A for ±12 VDC each slot

## Configurations

Model Number	Configuration
PCI-40A	4-slot PCI IndustryPack carrier with 8/32 MHz IndustryPack bus
<b>Associated Products</b>	
PCI-60A-8/32	6-slot PCI IndustryPack carrier with 8/32 MHz slots
C-IP50F-IP50F-3	Three foot 50 conductor ribbon cable
C-IP50F-IP50F-6	Six foot 50 conductor ribbon cable
IP-TERM	50-pin screw terminal block with ribbon cable header

\*A reduced memory map version of the PCI-40A is available by special order. Contact SBS at (651) 905-4700 for details.

#### Corporate Headquarters

2400 Louisiana Blvd. NE, #5-600  
Albuquerque, NM 87110-4316  
Tel 505.875.0600 Fax 505.875.0400  
Email info@sbs.com

#### European Headquarters

Memminger Str. 14  
D-86159 Augsburg, Germany  
Tel +49-821-5034-0 Fax +49-821-5034-119  
Email sales@sbs-europe.com



For additional contact information, please visit our web site at [www.sbs.com](http://www.sbs.com)

Specifications subject to change without notice. All trademarks and logos are property of their respective owners.  
©2002 SBS Technologies, Inc. 20020802