

RACK-300A

4U 14-Slot Chassis



RACK-300A



Top View

SPECIFICATIONS

- 4U height 19" Rack mounting chassis
- Plastic front panel with lockable door to protect the running system
- Two reset switches for dual system applications
- AT type KBD connector on front panel with cap protection
- Drive Bays: — 2 x 3.5" FDD
— 2 x 5.25" Drive
- One 12cm cooling fan with removable filter
- Designed with anti-vibration card clamp to keep system stable
- Supports AT/ATX form factor PC motherboard
- Supports backplane: BP-14S, BP-14SD, PCI-14S, PCI-14S2, PCI-13SD, PX-14S5, PX-14S2, IP-14S; PCI-8S or BP-8S, PCIAGP-7S, PXAGP-7S, (For RACK-300AxM version) PCIAGP-13S2, PCIAGP-13S3, PXAGP-12S2, PXAGP-13S, PXAGP-13S3
- Supports power supply: PS/2 size AT/ATX PSU
- Optional Sliding Rails Kit: 24" or 18"
- Vibration: 5 ~ 17Hz, 0.1" double amplitude displacement
17 ~ 640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Industrial Green (PANTONE 417C) or White (PANTONE 413C)
- Dimensions: 431(W) x 176(H) x 433(D)mm; (17" x 6.9" x 17")
- Net/GW (kg): 11/14

ORDERING INFORMATION


- RACK-300A[C]/ACE-925A: 4U 14-slot rackmount chassis with ACE-925A power supply
- RACK-300A[C]ATX/ACE-828A: 4U ATX MB rackmount chassis with ACE-828A power supply
- RACK-300A[C]R/ACE-C232: 4U 14-slot rackmount chassis with ACE-C232 redundant power supply
- RACK-300A[C]M/ACE-925A: 4U AT MB rackmount chassis with ACE-925A power supply

RACK-314A

4U 14-Slot All Full Length Cards Chassis



RACK-314AW



Dual Front Cooling Fan

SPECIFICATIONS

- 4U height 19" Rack mounting chassis
- Front panel with lockable door to protect the running system
- Two reset switches for dual system applications
- AT type KBD connector on front panel with key-lock
- The Bays : — 1 x 3.5" FDD — 1 x 5.25" Drive — 1 x 3.5" HDD
- Two 8cm cooling fans with removable filter
- Designed with an anti-vibration card clamp that keep the system stable
- Supports backplane : BP-14S, BP-14SD, PCI-14S, PCI-14S2, PCI-13SD, PX-14S5, PX-14S2, IP-14S, PCIAGP-13S2, PCIAGP-13S3, PXAGP-12S2, PXAGP-13S, PX-13S3
- Supports power supply: PS/2 size AT/ATX PSU
- Optional rack-mount slide: 24" or 18"
- Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- Dimensions: 431(W) x 176(H) x 413(D)mm; (17" x 6.9" x 16.3")
- Net/GW (kg): 12/15

ORDERING INFORMATION

- RACK-314A[C]/ACE-925A : 4U 14-slot rackmount chassis with ACE-925A power supply

RACK-360

4U 14-Slot Chassis



RACK-360



Top View

SPECIFICATIONS

- 4U height 19" Rack mounting chassis
- Front panel with lockable door to protect the running system
- AT type KBD connector on front panel
- Drive Bays : 1 x 3.5" FDD, 2 x 3.5" internal and 2 x 5.25" Drive
- One 12cm cooling fan with removable filter
- Designed with an anti-vibration card clamp that keep the system stable
- Supports backplane: BP-14S, BP-14SD, PCI-13SD, PCI-14S, PCI-14S2, PCI-14S3, PX-14S5, IP-13SD, IP-14S, PCIAGP-13S2/13S3, PXAGP-12S2/13S/13S3
- Supports power supply: PS/2 size AT/ATX PSU
- Vibration: 5 ~ 17Hz, 0.1" double amplitude displacement
17 ~ 640Hz, 1.5G acceleration peak to peak
- Shock: 10G acceleration peak to peak (11ms)
- Color: White (PANTONE 413C)
- Dimensions: 431(W) x 177(H) x 450(D)mm; (17" x 7" x 17.7")
- Net/GW (kg): 15/17

ORDERING INFORMATION

- RACK-360W/ACE-925A: 4U 14-slot rackmount chassis with ACE-925A power supply
- RACK-360WATX/ACE-828A: 4U 14-slot ATX MB rackmount chassis with ACE-828A power supply
- RACK-360WR/ACE-C232: 4U 14-slot rackmount chassis with ACE-C232 redundant power supply