

# Passive Backplanes

## 20-slot ISA/PCI Backplanes

Compatible with IPC Chassis: SPC-530, IPC-623, IPC-622, ACP-7000, ACP-5260

### PCA-6120P12-0A1

- Segments: 1
- Slots: 7 ISA, 11 PCI, 1 PICMG/PCI, 1 PICMG
- Size: 417 x 260 mm (16.42" x 10.24")
- PCI bridge: Pericom PI7C8150MA
- Primary PCI: 3 slots; Secondary PCI: 9 slots
- Ordering Information: PCA-6120P12-0A1



### PCA-6120P18-0A1

- Segments: 1
- Slots: 1 ISA, 17 PCI, 1 PICMG/PCI, 1 PICMG
- Size: 417 x 260 mm (16.42" x 10.24")
- PCI bridge: Three Pericom PI7C8150MA
- Secondary: 6 slot/6 slot/6 slot
- Ordering Information: PCA-6120P18-0A1



### PCA-6120DP4-0B1


- Segments: 2
- Slots: 7 ISA, 6 PCI, 2 PICMG/PCI, 4 PICMG
- Size: 420 x 260 mm (16.42" x 10.24")
- Ordering Information: PCA-6120DP4-0B1



## 64-bit ISA/PCI Backplanes

### PCA-6108P6X-0A1

- Segments: 1
- Slots: 6 PCI, 2 PICMG
- Size: 180 x 282 mm (7.09" x 11.1")
- PCI bridge: Intel® 21154
- Primary (64-bit/66 MHz): 3 slots
- Secondary (64-bit/33 MHz): 4 slots
- Jumper selectable 1: VI/O 3.3 V or 5V
- Jumper selectable 2: PCI bus 33 MHz or PCI bus 66 MHz
- Chassis: IPC-6908, IPC-6608
- Ordering Information: PCA-6108P6X-0A1



### PCA-6113P7X

- Segments: 1
- Slots: 4 ISA, 7 PCI, 2 PICMG
- Size: 315 x 300 mm (12.4" x 11.8")
- PCI bridge: Intel® 21154
- Primary (64-bit/66 MHz): 3 slots; Secondary (64-bit/66 MHz): 4 slots
- Jumper Selectable 1: VI/O 3.3 V or 5 V
- Jumper selectable 2: PCI bus 33 MHz or PCI bus 66 MHz
- Chassis: IPC-616, IPC-615, IPC-611, IPC-610, ACP-4000
- Ordering Information: PCA-6113P7X



### PCA-6114P12X-A1

- Segments: 1
- Slots: 1 ISA, 11 PCI, 1 PICMG/PCI, 1 PICMG
- Size: 315 x 260 mm (12.4" x 10.24")
- PCI bridge: Intel® 21154
- Secondary (64-bit/66 MHz): 4 slots
- Secondary (64-bit/33 MHz): 8 slots
- Chassis: IPC-616, IPC-615, IPC-611, IPC-610, ACP-4000
- Ordering Information: PCA-6114P12X-A1



### PCA-6119P16X

- Segments: 1
- Slots: 1 ISA, 16 PCI, 2 PICMG
- Size: 417 x 300 mm (16.4" x 11.8")
- PCI bridge: Three Intel® 21154
- Secondary (64-bit/66 MHz): 4 + 3 slots
- Secondary (64-bit/33 MHz): 9 slots
- Jumper selectable 1: VI/O 3.3 V or 5V
- Jumper selectable 2: PCI bus 33 MHz or PCI bus 66 MHz
- Chassis: IPC-623, IPC-622, ACP-7000, ACP-5260
- Ordering Information: PCA-6119P16X

