

DEVICENET ISA INTERFACE CARD

Overview

The SST DeviceNet ISA interface card connects your ISA bus computer to DeviceNet.

Applications

Many third party software programs support the SST DeviceNet interface card for various applications including:

- Operator Interface and HMI
- PC Control
- Network Configuration, Troubleshooting and Diagnostics
- I/O Emulation
- Device Development

Features

- Entire DeviceNet Protocol is executed in hardware
- UCMM capable, Group 1, 2, and 3 dynamic explicit connections supported
- Simultaneous execution of Group 2 Client (master) and Server (slave) operation
- All DeviceNet standard baud rates supported: 125, 250, and 500 Kbaud
- Full DeviceNet implementation including Change of State (COS) and explicit messaging
- DeviceNet compliance is ensured at the card level for I/O scanner and device applications

Custom Driver Development

SST provides an open documented memory map interface with example C source code and Windows 32-Bit DLLs and drivers.



Included with SST DeviceNet ISA Interface Card

- DeviceNet Network Analyzer and Monitor Diagnostic Software Tools
- DeviceNet Node Commissioning Tool
- OPC Server
- Custom driver development software
- Microsoft Windows 2000/NT/XP drivers/DLLs
- 24/7 global technical support

DeviceNet
CONFORMANCE TESTED



SST
TM

Network Interface Cards

www.mySST.com

Hardware Specifications

- 16 bit, half-length interface card, surface-mount technology ISA interface card
- Compatible with ISA (PC/AT) bus
- 256 Kbytes shared RAM (16 Kbytes host interface window)
- High performance 40 MHz processor with 512 Kbytes RAM, 512 Kbytes Flash
- Software configurable interrupts, 2/9, 5, 7, 10, 11, 12, and 15 supported
- DeviceNet compatible 5-pin DeviceNet connector
- DeviceNet compatible network status bicolor indicator
- Supports connection to non-powered (3 wire) CAN network with external 12-24 VDC supply
- Compatible with CAN specification 2.0 part A
- Supports CAN data rates up to 1 Mbaud
- Supports all standard DeviceNet data rates: 125, 250, and 500 Kbaud
- Multiple cards can be configured in the same computer
- 500 V optically isolated CAN interface
- Operational temperature: 0 to 50 C (32 to 122°F)
- Storage temperature: -25 to 70C (-13 to 158°F)
- Power requirements: +5 V +/- 5% 325 mA (typical)

Other Reference Materials

Web Site

- www.mysst.com/cards/devicenet/dn.htm

Related DeviceNet Products

- Network Interface Cards connect various computer bus formats to industrial networks
- Network Diagnostic and Configuration Software
- Network Gateways
- PLC Network Modules connect programmable controllers to industrial networks and I/O devices
- Data Servers include OPC and DDE Servers

Certifications

- DeviceNet Conformance Tested

Affiliations

- Active member of the Open DeviceNet Vendor Association (ODVA)

Ordering Information

- Order part number 5136-DNP-ISA

Also available from SST:

**Gateways
PLC Modules
Data Servers
Interface Cards
Embedded Solutions
I/O Simulation Software
Diagnostic and Configuration Software**

www.mysst.com

EDNPISA

October 2002

50 Northland Road
Waterloo, Ontario
Canada N2V 1N3
Tel: 519-725-5136
Fax: 519-725-1515
Sales@mysst.com

W Woodhead Connectivity
applcom • Brad Harrison • mPmi • NetAlert • RJ-Lxxx • SST
THE GLOBAL LEADER IN INDUSTRIAL COMMUNICATIONS AND CONNECTIVITY