



Feature

- ✦ Front Panel NEMA 4 & IP 65 rating (Panel –mounted)
- ✦ Ethernet
- ✦ 2 PCI expansion slots / 2 x USB 2.0 ports
- ✦ 2 Serial Ports (one is reserved for touchscreen)

LCD Display

- ✦ 15" SVGA 1024 x 768
- ✦ 16.2M Colors, 400cd/m² Luminance
- ✦ View angle : (H) 170°, (V) 135°

Mechanical Specifications

Construction: Heavy-duty steel chassis, NEMA 4 / IP-65 rating front panel

Front Panel Beige

Color:

Mounting: Panel Mount

Operating 0-50°C

Temperature:

Storage -10°C - 75°C

Temperature:

Vibration: 5 - 17HZ, 0,1" double amplitude displacement, 17 - 640HZ, 1.5G acceleration peak to peak

Shock: 10G acceleration peak to peak (11ms)

EMC: FCC/CE Class A certified

Power Supply: AC Universal input 220W ATX PSU

System Specifications

CPU Intel® Celeron M; ULV 600MHz (non L2 cache)

Type/Speed:

Chipset: Intel® 852GM + ICH4

Memory: DDR266 SDRAM, Max 1 GB

DRAM Socket: 1 x 200-pin SO-DIMM

Hard Drive: 1 x 2.5" Slim Type

BIOS: Phoenix-Award 2MB PnP BIOS

IDE Interface: UDMA 33/66/100 x 1

Watchdog: 1 ~ 255 secs Watchdog timer, with Rest, with NMI

I/O port: 2 x Com ports, 1 x SPP/ECP/EPP, 2 x USB 2.0, 2 x PS/2 keyboard and mouse ports

RJ-45 LAN Port: Intel® 82562EM (10/100Mbps)
support Wake-On-LAN w/ATX power

VGA: Built-in Intel® 825GM

Expansion Slots: 2 x PCI Slots

Touchscreen Resistive

(optional):