

» CP308 «



Intel® Core™ 2 Duo 3U CompactPCI CPU board

» **Highest performance based on latest 45nm technology**

Intel® Core™ 2 Duo processor up to 2.26 GHz

» **Latest DDR3 memory technology**

Providing memory throughput (up to 17 GB/s)

» **Comprehensive I/O capabilities**

Gigabit Ethernet, USB, VGA, SATA, RAID, USB NAND Flash ...

Technical Information

Processor	Intel® Core™2 Duo processor in SFF (Small Form Factor) BGA package (45nm manufacturing process): <ul style="list-style-type: none"> - Core™2 Duo SP9300, 2.26 GHz, 1066 MHz FSB, 6 MB L2 cache - Core™2 Duo SL9400, 1.86 GHz, 1066 MHz FSB, 6 MB L2 cache - Core™2 Duo SU9300, 1.2 GHz, 800 MHz FSB, 3 MB L2 cache All board versions are passive cooled with a heatsink within 4HP height Forced air cooling at a specific flow rate is required depending on the processor version
Memory	
System Memory:	Up to 8GByte dual channel DDR3 1066 MHz memory, without ECC, Both channels realized as SODIMM sockets
USB Flash:	Up to 16GB USB NAND Flash module
Flash (uEFI):	Two redundant 4 MByte SPI Flashes
EEPROM:	Serial EEPROM (24LC64)
Compact Flash:	Onboard CompactFlash mounting within 8HP mezzanine
HDD:	Onboard 2.5" SATA HDD mounting within 8HP mezzanine
Onboard Controller	
GMCH Graphic Memory Controller Hub:	Intel® GS45 (Small Form Factor) Dual-channel DDR3 memory controller (800/1066 MHz) Internal graphics controller (two engines) or PCIe x16 port
I/O Controller Hub:	Intel® ICH9M SFF 4 x SATA II ports with RAID functionality (0,1) 8 x USB 2.0, 6 x PCI-Express x1, LPC, SPI, HDA (High Definition Audio) 1x 32-bit/33MHz PCI master interface
VGA:	Integrated in GS45 max. 2048 x 1536 pixels (QXGA), 16M colors, @75Hz, CRT, max. 384MByte used from system memory
Gigabit Ethernet:	2 x GbE Front or Rear (s/w switchable), 82574L PCI-Express controller, WOL (Wake-On-LAN) support
Super I/O:	LPC Super I/O SMC SCH3112I-NU with 2x UART and PS/2
Watchdog:	Two-stage Watchdog with programmable timeout ranging from 125ms to 4096s in 16 steps FPGA-based, software configurable
Trusted Platform Module (TPM):	Chipset integrated TPM, Compliant to Trusted Computing Group TPM Specification revision 1.2
System Management Controller:	NXP LPC2136 32bit controller with on-chip 256 kB Flash and 32 kB RAM, External 512 kbit EEPROM
Front Panel Interfaces	
VGA:	1 x VGA-CRT 15-pin D-Sub connector
USB:	2 x USB 2.0 ports, 4-pin standard USB connectors
LEDs:	4 x bicolor control and status LEDs, 1x bicolor SMC LED, 1x Thermal and 1x Watchdog LED
Ethernet:	2 x RJ45 with integrated LEDs (ACT, SPEED)
Onboard Interfaces	
USB Flash:	1 x USB port routed to a dedicated onboard connector for mounting an optional USB NAND Flash module
Serial ATA:	4 x Serial ATA II ports: 2 x ports are fixed to onboard standard SATA connectors, 2 x ports can be switched either to the I/O extension or to rear I/O
I/O Extension Connector (to 8HP):	I/O Extension connector holds the following interfaces: 2 x SATA, 3 x USB, 4x PCIe x1 or 1x PCIe x4, HDA, PS/2, COM
High Speed Graphics Extension Connector (to 8HP):	2 x Display Port (DP), 2x HDMI, SDVO and PCIe x16 graphics port (the pins are multiplexed and not all interfaces can be used simultaneously)
Rear I/O via J2	The Rear I/O versions support: <ul style="list-style-type: none"> - Two Gigabit Ethernet ports without LED - Two SATA interfaces - Two USB 2.0 ports - Two COM ports (3.3V TTL signalling) - One CRT VGA port - One fan control input - One power management output - Monitor and control signals for fan and power supply
CompactPCI Bus Interface	PICMG 2.0 Rev. 3.0 compatible, 32-bit/33MHz, version with rear I/O on J2 PICMG 2.0 Universal 5V and 3.3V PCI signalling voltage supported, 7 Req/Gnt & clock lines Operating in system slot as system master and in peripheral slot in PCI passive mode
Supervisory Functions	Watchdog, software configurable, 125ms to 4096s, generates IRQ or hardware reset. Firmware to read temperatures and onboard voltages, control fan speeds
Hot Swap	Support for all signals to allow peripheral boards to be hot swapped. The individual clocks for each slot and access to the backplane ENUM# signal comply with the PICMG 2.1 Hot-Swap specification.
Compliance	CompactPCI Core Specification PICMG 2.0 Rev. 3.0 CompactPCI Hot Swap Specification PICMG 2.1 R2.0 Designed to meet or exceed: <ul style="list-style-type: none"> - Safety: UL 60950-1, CSA 22.2 No 60950, EN 60950-1, IEC 60950-1 - EMI/EMC: EN 55022 / EN 55024, EN 61000-6-3 / EN 61000-6-2
General	
Dimensions:	100 x 160mm, 3U, 4HP
Weight:	460g / 4HP
MTBF:	219,495 h acc. to MIL-HDBK-217 FN2, Ground Benign GB, controlled at 30°

CP308-MEDIA

Technical Information

Onboard Controller

HD Audio	AD1884A HD audio codec supporting the following ports: Mic-In stereo port, Line-In stereo port, Line-Out stereo port, S/P-DIF-Out digital port, CD-In stereo port, Internal line-out mono port
----------	---

Front Panel Interfaces

DisplayPort	2 x 20-pin DisplayPort connectors, DVI/HDMI capable through passive cable adapter
Mic-In	1 x 3.5 mm stereo jack, pink
Line-In	1 x 3.5 mm stereo jack, blue
Line-Out	1 x 3.5 mm stereo jack, green, with headphone detection
S/P-DIF-Out	1 x optical fiber connector (Toslink)

Onboard Interfaces

Serial ATA	1 x SATA connector for connecting a SATA 2.5" HDD/SSD
CompactFlash	1 x CompactFlash card socket, CF Type I and II supported
SD/SDHC	1 x SD/SDHC card socket
PCI Express Mini Card	1 x PCI Express Mini Card socket, with support for PCIe x1 or USB 2.0
Serial Port	1 x 10-pin connector, RS232
CD-In	1 x 4-pin connector, stereo port
Line-Out	1 x 2-pin connector, mono port

General

Dimensions	100 x 162mm, 4HP (extends CP308 to 8HP)
Weight	585 grams (CP308 with CP308-HDD)
MTBF	978,674 h acc. to MIL-HDBK-217 FN2, Ground Benign, controlled at 30°

Software Support

Windows XP, Windows XP embedded, Windows Vista, Windows 7, Linux

Power Consumption

typ. 1.5W, without peripheral devices connected

Environmental

Operating temp.	0°C to +60°C standard, -40°C to +85°C with special screened version
Storage Temp.	-55°C to +85°C
Humidity	93% RH at 40 °C, non-condensing (acc. to IEC 60068-2-78)

CP308-HDD

Technical Information

Front Panel Interfaces

DVI	1 x 29-pin DVI-D connector
USB	2 x USB 2.0 ports, 4-pin standard USB connectors
COM	1 x 9-pin D-Sub connector, RS232 signaling
PS/2	1 x 6-pin shielded mini-DIN connector for keyboard and mouse
Control	Reset button and HDD LED

Onboard Interfaces

USB NAND Flash	Up to 16GB USB NAND Flash module
Serial ATA	1 x SATA connector for connecting a SATA 2.5" HDD/SSD
CompactFlash	1 x CompactFlash card socket, Type I and II supported

General

Dimensions	100 x 158mm, 4HP (extends CP308 to 8HP)
Weight	590 grams (CP308 with CP308-HDD)
MTBF	1,230,723 h acc. to MIL-HDBK-217 FN2, Ground Benign, controlled at 30°

Technical Information

Software Support	Windows XP, Windows XP embedded, Windows Vista, Windows 7, Linux, VxWorks
Power Consumption	typ. 1W, without peripheral devices connected
Environmental	
Operating temp.	0°C to +60°C standard, -40°C to +85°C with special screened version
Storage Temp.	-55°C to +85°C
Humidity	93% RH at 40 °C, non-condensing (acc. to IEC 60068-2-78)

Ordering Information

Article	Description
Standard Configurations	
CP308-1.2D-4GD-4HP-R-UF4-E2	1.2GHz Core 2 Duo ULV, 2x 2GB SODIMM DDR3, 4HP, Rear I/O, 4GB USB Flash, extended temp. E2
CP308-1.2D-4GD-4HP-R-UF8-E2-CC	1.2GHz Core 2 Duo ULV, 2x 2GB SODIMM DDR3, 4HP, Rear I/O, 8GB USB Flash, extended temp. E2, with coating
CP308-1.2D-4GD-8HP-F-CF4-E2-CC	1.2GHz Core 2 Duo ULV, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O, 4GB CompactFlash, extended temp. E2, with coating
CP308-1.2D-4GD-8HP-F-E2	1.2GHz Core 2 Duo ULV, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O, extended temp. E2
CP308-1.2D-8GD-8HP-F-E2	1.2GHz Core 2 Duo ULV, 2x 4GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O, extended temp. E2
CP308-1.86D-4GD-4HP-F	1.86GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 4HP, Front I/O
CP308-1.86D-4GD-4HP-R	1.86GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 4HP, Rear I/O
CP308-1.86D-4GD-8HP-F	1.86GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O
CP308-1.86D-4GD-8HP-F-CF2-CC	1.86GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O, 2GB CompactFlash, with coating
CP308-1.86D-4GD-8HP-R	1.86GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Rear I/O
CP308-2.26D-4GD-4HP-F	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 4HP, Front I/O
CP308-2.26D-4GD-4HP-R	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 4HP, Rear I/O
CP308-2.26D-4GD-4HP-R-UF8	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 4HP, Rear I/O, 8GB USB Flash
CP308-2.26D-4GD-8HP-F	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O
CP308-2.26D-4GD-8HP-F-CC	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O, with coating
CP308-2.26D-4GD-8HP-F-CF2	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O, 2GB CompactFlash
CP308-2.26D-4GD-8HP-F-CF2-HDDXL	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Front I/O, 2GB CompactFlash, 2.5" SATA HDD
CP308-2.26D-4GD-8HP-R	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Rear I/O
CP308-2.26D-4GD-8HP-R-HDDXL	2.26GHz Core 2 Duo, 2x 2GB SODIMM DDR3, 8HP with CP308-HDD, Rear I/O, 2.5" SATA HDD
CP308-2.26D-8GD-4HP-R	2.26GHz Core 2 Duo, 2x 4GB SODIMM DDR3, 4HP, Rear I/O
Rear Transition Modules	
CP-RI03-04	4HP rear I/O module (2x Ethernet, 2x USB, VGA, 2x SATA connectors)
CP-RI03-04	8HP rear I/O module (additional to 4HP COM1/2)
CP-RI03-04S	4HP rear I/O module (2x Ethernet, COM, VGA, 2x SATA connectors)
Software¹⁾	
VXW-BSP-CP308-V6.8	VxWorks 6.8 Board Support Package, CP308 User's Manual
Notes:	¹⁾ Windows and Linux BSP's only available as download on the web page

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany

Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 279
info@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA

Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building, Block #1, ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China

Tel.: + 86 10 63751188
Fax: + 86 10 83682438
info@kontron.cn

