

PS/2 AC Input AT Type

ACE-T140A

400 W PS/2 Type AT Power Supply



Specifications

Input Type	95~264VAC Full Range			
Output Voltage	+5 V	+12 V	-5 V	-12 V
	42.0 A (2.0 A min.)	15 A (1.0 A min.)	0.3 A (0 A min.)	0.8 A (0 A min.)
Efficiency	75%			
Temperature	Operating: 0°C ~ 50°C, Storage: -20°C ~ 80°C			
MTBF	100,000 hr			
Output Connector	1 x P8+P9, 6 x HDD, 2 x FDD			
Dimensions	140 mm x 150 mm x 86 mm			

Ordering Information

Part No.	Description
ACE-T140A-RS	400 W AC-DC PS2 AT Power Supply, with PFC

ACE-935AL

300 W PS/2 Type AT Power Supply



Specifications

Input Type	85 ~ 140 VAC, 170 ~ 270 VAC Auto Range					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
		40 A (3A min)	8 A (0.1A min)	0.3 A	0.7 A	
Efficiency	68%					
Temperature	0°C ~ 50°C (Operating), -40°C ~ 75°C(Storage)					
MTBF (hrs)	100,000					
Output Connector	1 x P8+P9, 1 x Extra +5V (P10), 5 x HDD/CDROM, 2 x FDD					

Ordering Information

Part No.	Description
ACE-935AL-RS	300 W AC-DC PS/2 AT Power Supply, AC select switch

ACE-925AP-U

250 W PS/2 Type AT Power Supply



High reliability magnetic bearing cooling system features low noise, high operating temperature and longer MTBF



Specifications

Input	Voltage	90 ~ 265 VAC Full Range			
	Frequency	47 ~ 63 Hz			
Output	Voltage	+5 V	+12 V	-5 V	-12 V
	Max. load	22 A	11 A	0.5 A	0.7 A
General	MTBF	100,000 hours			
	Temperature	Operating: 0°C ~ 50°C Storage: -25°C ~ 70°C			
	Dimensions	140 x 150 x 86 (mm)			
	Output Connector	1 x P8+P9, 4 x HDD/CDROM, 2 x FDD, 2 x SATA			

Ordering Information

Part No.	Description
ACE-925AP-U-RS	250 W AC-DC PS/2 AT Power Supply, with PFC

1

Industrial
Computing
Solutions

2

Video
Capture
Solutions

3

Embedded
Computing
Solutions

4

O/Ring
Network
Communication

5

Power Supply/
Peripherals

6

Panel
Solutions
Introduction