

RACK-810/814 RACK-3025A

10/14-Slot full size industrial chassis

4U Height 10-Slot Full Size Industrial PC Chassis With Redundant Power Supply Case

RACK



RACK-810



RACK-814



RACK-3025AW



RACK-3025AB

ACE-RC02
Dual Redundant
Power Supply Case

SPECIFICATIONS

- ◆ 4U height 19" Rack mounting chassis
- ◆ Front panel with lockable door to protect the running system
- ◆ Bracket area is located in the front for easy access to the cables
- ◆ One USB port on front panel
- ◆ Drive Bays:
RACK-810: 2 x 5.25 Drive, 1 x 3.5 FDD/HDD Drive
RACK-814: 1 x 3.5" FDD, 1 x 5.25" Drive, 1 x 3.5" HDD
- ◆ Three hot-removable 8cm cooling fans
- ◆ Designed with anti-vibration card clamp to keeping system stable
- ◆ Supports ATX form factor PC motherboard(RACK-814)
- ◆ Supports backplane :
RACK-810: BP-10S,BP-10SD,PCI-10S,PX-10S,IP-10S,IPX-9S,IPX-9S,PCIAG-9S2,PXAGP-9S
RACK-814: BP-14S,BP-14SD,PCI-13SD,PCI-14S,PCI-14S2,PCI-14S3, PX-14S5,IP-13SD,IP-14S,IPX-13S,PCIAGP-13S2,PCIAGP-13S3,PXAGP-12S2,PXAGP-13S,PXAGP-13S3
- ◆ Supports power supply: PS/2 size AT/ATX PSU (ACE-93x/92x/916V series and ACE-828 series) or ACE-C232 mini redundant PSU
- ◆ Optional rack-mount slide: 24" or 18"
- ◆ Vibration: 5~17Hz, 0.1" double amplitude displacement 17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock: 10G acceleration peak to peak (11ms)
- ◆ Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- ◆ Dimensions: 431(W) x 176(H) x 465.4(D)mm; (17" x 6.9" x 18.3")
- ◆ Net/GW (kg): 13/18

ORDERING INFORMATION

- RACK-814[C]/ACE-925A :
4U 14-slot rackmount chassis with ACE-925A power supply
 - RACK-814[C]ATX/ACE-828A :
4U ATX MB rackmount chassis with ACE-828A power supply
 - RACK-814[C]R/ACE-C232 :
4U 14-slot rackmount chassis with ACE-C232 redundant power supply
 - RACK-810[C]/ACE-832A
4U 10-slot rackmount chassis with ACE-832A Power supply
- [C] Color Code : B = Black, W = White P Power Supply
- SLIDE-18: 18" rack-mount slide
 - SLIDE-24: 24" rack-mount slide
 - EXTENDER-6: 6" extender for 18" or 24" slide

SPECIFICATIONS

- ◆ 4U height 19" Rack mounting chassis
- ◆ Front panel with lockable door to protect the running system
- ◆ Two reset switches for dual system applications
- ◆ AT type KBD connector on front panel
- ◆ Drive Bays: 1 x 3.5" FDD 3 x 5.25" Drive
- ◆ Two 8cm cooling fans with removable filter
- ◆ Designed with anti-vibration card clamp to keep system stable
- ◆ Supports backplane: BP-10S, BP-10SD, PCI-10S, IP-10S, PCIAGP-9S2,PXAGP-9S
- ◆ Supports 10 full size cards
- ◆ Built-in ACE-RC02 redundant power case
- ◆ Supports power supply:
ACE-R20 series redundant power module
- ◆ Optional rack-mount slide : 24"
- ◆ Vibration: 5~17Hz, 0.1" double amplitude displacement 17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock: 10G acceleration peak to peak (11ms)
- ◆ Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- ◆ Dimensions: 431(W) x 176(H) x 511(D)mm; (17" x 6.9" x 20.1")
- ◆ Net/GW (kg): 17/22

ORDERING INFORMATION

- RACK-3025A[C] :
4U 10-slot rackmount chassis with ACE-RC02 power supply case
- [C] Color Code : B = Black; W = White
- ACE-R20A:
AC input redundant power module for RACK-3025A
 - ACE-R20T:
48V DC input redundant power module for RACK-3025A
 - ACE-R20C:
24V DC input redundant power module for RACK-3025A
(Please select one or two ACE-R20 series power module for each RACK-3025A chassis)

Option:

- SLIDE-24: 24" rack-mount slide
- EXTENDER-6: 6" extender for 18" or 24" slide