

ET 16 INDICATING LAMP (INCANDESCENT)				RESISTOR ONLY		BULB			
				165A7844P*		GE			
116B6708G	*	*		RATED	MIN	MAX	PART NO.	OHMIC VALUE	CAT NO.
	1			24 DC	22	28	1	10	1819
	2			48 DC	44	56	2	200	1835
	3			125DC	110	140	3	2000	1835
	4			250DC	220	280	4	5100	1835
	5			120AC	95	130	5	1900	1835
	6			240AC	195	260	6	4800	1835
	7			70AC	55	76	7	750	1835
	8			130AC	105	140	13	2300	1835
					COLOR CAP				
CAPS ONLY				* NONE					
286A5443PC4				C CLEAR TRANSPARENT					
286A5443PR5				R RED TRANSLUCENT					
286A5443PG5				G GREEN TRANSLUCENT					
286A5443PY5				Y YELLOW TRANSLUCENT					
286A5443PW5				W WHITE TRANSLUCENT					
286A5443PB4				B BLUE TRANSPARENT					
286A5443PA4				A AMBER TRANSPARENT					
286A5443PG4				D GREEN TRANSPARENT					
286A5443PR4				E RED TRANSPARENT					

ET 16 FOR DIM-BRIGHT APPLICATION				RESISTOR						
				165A9217P		RESISTANCE OHMS				
127B8108G	*	*		RATED	MIN	MAX	PART NO.	TOTAL	TAPS	BULB GE CAT NO.
	1			48 DC	44	56	1	450	50	1835
	2			125 DC	110	140	2	2550	1700	1835
	3			250 DC	220	280	3	6000	4400	1835
	4			120 AC	95	130	4	2450	1600	1835
	5			240 AC	195	260	5	5700	4200	1835
				COLOR CAP						
				* NONE						
				C CLEAR TRANSPARENT						
				E RED TRANSLUCENT						
				A AMBER TRANSLUCENT						

ET 17 INDICATING LAMP (NEON)				RESISTOR		BULB		
				165A7956P		GE		
116B6734G	*	*		VOLTAGE RANGE		PART NO.	OHMIC VALUE	CAT NO.
	1			AC/DC				
	2			110-139		1	220 K	B1A
	3			140-219		2	560 K	B1A
	4			220-299		3	820 K	B1A
	5			300-374		4	1 Meg	B1A
	6			375-449		5	1.2 Meg	B1A
				450-600		6	1.6 Meg	B1A
				COLOR CAP				
				* NONE				
				C CLEAR TRANSPARENT				
				E RED TRANSLUCENT				
				A AMBER TRANSLUCENT				

ORDERING TABLE COLOR CAPS		
ET-16 & ET-17		
PART NO.	COLOR	
286A5443PC4	CLEAR TRANSPARENT	
286A5443PR5	RED TRANSLUCENT	
286A5443PG5	GREEN TRANSLUCENT	
286A5443PY5	YELLOW TRANSLUCENT	
286A5443PW5	WHITE TRANSLUCENT	
286A5443PA4	AMBER TRANSPARENT	
286A5443PG4	GREEN TRANSPARENT	
286A5443PR4	RED TRANSPARENT	

ET 5 INDICATING LAMP (ONE BRILLIANCY)						
6015700G	* *	CIRCUIT VOLTAGE			UP TO 1/4	9/32 TO 2
		RATED	MIN	MAX	IN. PANEL	IN. PANEL
	1	24 DC	22	28	X	
	2	48 DC	44	56	X	
	3	125DC	110	140	X	
	4	250DC	220	280	X	
	9	115AC	95	125	X	
	10	230AC	190	250	X	
	19	24 DC	22	28		X
	20	48 DC	44	56		X
	21	125DC	110	140		X
	22	250DC	220	280		X
	27	115AC	95	125		X
	28	230AC	190	250		X
	70	67AC	54	75	X	
	71	67AC	54	75		X

COLOR CAP		
CAPS ONLY	*	NONE
286A5443PC4	C	CLEAR TRANSPARENT
286A5443PR5	R	RED TRANSLUCENT
286A5443PG5	G	GREEN TRANSLUCENT
286A5443PY5	Y	YELLOW TRANSLUCENT
286A5443PW5	W	WHITE TRANSLUCENT
286A5443PB4	B	BLUE TRANSPARENT
286A5443PA4	A	AMBER TRANSPARENT
286A5443PG4	D	GREEN TRANSPARENT
286A5443PR4	E	RED TRANSPARENT

ET 6 INDICATING LAMP (ONE BRILLIANCY)					
6015700G	* *	CIRCUIT VOLTAGE			UP TO 1/4
		RATED	MIN	MAX	IN. PANEL
	41	24 DC	22	28	X
	42	48 DC	44	56	X
	43	125DC	110	140	X
	44	250DC	220	280	X
	49	115AC	95	125	X
	50	230AC	190	250	X
	72	67AC	54	75	X

ET 5 INDICATING LAMP (DIM BRIGHT)						
		CIRCUIT VOLTAGE			UP TO 1/4 IN. PANEL	9/32 TO 2 IN. PANEL
6015700G	*	RATED	MIN	MAX	X	
	6	48 DC	44	56	X	
	7	125DC	110	140	X	
	8	250DC	220	280	X	
	13	115AC	95	125	X	
	14	230AC	190	250	X	
	24	48 DC	44	56		X
	25	125DC	110	140		X
	26	250DC	220	280		X
	31	115AC	95	125		X
	32	230AC	190	250		X

ET 6 INDICATING LAMP (DIM BRIGHT)						
		CIRCUIT VOLTAGE			UP TO 1/4 IN. PANEL	
6015700G	*	RATED	MIN	MAX	X	
	46	48 DC	44	56	X	
	47	125DC	110	140	X	
	48	250DC	220	280	X	
	53	115AC	95	125	X	
	54	230AC	190	250	X	

ET 5 INDICATING LAMP (DIM BRIGHT)						
		CIRCUIT VOLTAGE			UP TO 1/4 IN. PANEL	9/32 TO 2 IN. PANEL
6015700G	*	RATED	MIN	MAX	X	
	6	48 DC	44	56	X	
	7	125DC	110	140	X	
	8	250DC	220	280	X	
	13	115AC	95	125	X	
	14	230AC	190	250	X	
	24	48 DC	44	56		X
	25	125DC	110	140		X
	26	250DC	220	280		X
	31	115AC	95	125		X
	32	230AC	190	250		X

COLOR CAP		
CAPS ONLY	*	NONE
286A5443PC4	C	CLEAR TRANSPARENT
286A5443PR5	R	RED TRANSLUCENT
286A5443PG5	G	GREEN TRANSLUCENT
286A5443PY5	Y	YELLOW TRANSLUCENT
286A5443PW5	W	WHITE TRANSLUCENT
286A5443PB4	B	BLUE TRANSPARENT
286A5443PA4	A	AMBER TRANSPARENT
286A5443PG4	D	GREEN TRANSPARENT
286A5443PR4	E	RED TRANSPARENT

ET 6 INDICATING LAMP (DIM BRIGHT)					
		CIRCUIT VOLTAGE			UP TO 1/4 IN. PANEL
6015700G	*	RATED	MIN	MAX	X
	46	48 DC	44	56	X
	47	125DC	110	140	X
	48	250DC	220	280	X
	53	115AC	95	125	X
	54	230AC	190	250	X