

WS-843A

12.1" TFT LCD 10-Slot Industrial Workstation

Analog VGA Input



OSD (On Screen Display)



SPECIFICATIONS

- ◆ 19" Rackmount, 7U height industrial workstation
- ◆ DM-121 12.1" LCD Module
 - Resolution : 800 x 600
 - Colors : 262K (18 bits colors)
 - Brightness : 250cd/m²
 - LCD MTBF : 50,000 hours
 - Backlight MTBF : 25,000 hours
 - Interface : Analog VGA input with OSD(ON Screen Display function)
- ◆ Membrane Keypad :
 - Keypad : 59 keys include 10 function keys
- ◆ Front door protected area :
 - 1 x 3.5" FDD
 - 1 x 5.25" CD-ROM
 - System power switch
 - One USB port
- ◆ Drive Bays :
 - 1 x 3.5" FDD
 - 1 x 5.25" CD-ROM
 - 1 x 3.5" HDD
- ◆ Built-in PS/2 interface touch pad on front panel
- ◆ One 12cm ball bearing cooling fan with filter
- ◆ Designed with an anti-vibration card clamp that keeps the system stable
- ◆ Optional Backplane :
 - BP-10S/ 10SD, PCI-10S/ 10S2, PX-10S, IP-10S/ 10S2, PCIAGP-9S2, PXAGP-9S
- ◆ ACE-832AP 300W ATX power supply with PFC function
- ◆ Optional power supply: PS/2 size AT/ATX PSU
- ◆ Optional 3M resistive type touch screen with RS-232 interface
- ◆ Operating temperature : 0°~ 50°C
- ◆ Relative Humidity : 5 ~ 85%, non-condensing
- ◆ Vibration:
 - 5~17Hz, 0.1" double amplitude displacement
 - 17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : White (PANTONE 413C)
- ◆ Dimension : 483(W) x 310(H) x 266(D)mm
- ◆ Net/GW: 14/18 (kg)

ORDERING INFORMATION

◆ WS-843AW-R2/ACE-832AP

7U 10 slot 12.1" TFT LCD workstation with ACE-832AP 300W ATX with PFC power supply

Option: T-R121B 3M Micro Touch Resistive touch screen

MPC-6022A

5U Height 14-Slot Industrial PC Chassis

Analog VGA Input



OSD (ON Screen Display) Control Key



- ◆ Supports ATX form factor PC motherboard
- ◆ Optional Backplane :
 - PCI-14S3, PCI-14S2, PCI-14S, PX-14S5, PX-14S3, PX-14S2, IP-14S3, IP-14S, BP-14S/SD2/SD/15S, PCI-13SD, IP-13SD, IPX-13S, PCIAGP-13S2, PCIAGP-13S3, PXAGP-12S2, PXAGP-13S, PXAGP-13S3
- ◆ Supports power supply :
 - PS/2 size AT/ATX power supply
 - ACE-R30A redundant power supply
- ◆ Optional Slide : 24" or 18"
- ◆ Vibration: 5 ~17Hz, 0.1" double amplitude displacement
17 ~ 640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : White (PANTONE 413C)
- ◆ Dimension : 431(W) x 220(H) x 470(D)mm;(17"x8.7"x18.5")
- ◆ Net/GW: 15/18 (kg)

SPECIFICATIONS

- ◆ 5U height 19" Rack mounting chassis
- ◆ Front panel with lockable door to protect disk access, power on/off and reset switch
- ◆ LCD monitor module:
 - 12.1" high Brightness TFT
 - 800x600 resolution
 - Brightness : 250 cd/m²
 - LCD interface: Analog VGA Signal input
- ◆ Drive Bays :
 - 1 x 3.5" FDD
 - 1 x 5.25" CD-ROM
 - 1 x 3.5" HDD
- ◆ Two 12cm ball bearing cooling fans
- ◆ Designed with anti-vibration card clamp to keep system stable

ORDERING INFORMATION

◆ MPC-6022AW-R2/ACE-832A

5U 14-slot rackmount chassis with 12.1" LCD and ACE-832A 300W power supply

◆ MPC-6022AWR-R2/ACE-R30A

5U 14-slot rackmount chassis with 12.1" LCD and ACE-R30A redundant power supply

◆ MPC-6022AWATX-R2 /ACE-[P]

5U ATX MB rackmount chassis with 12.1" LCD and ACE-[P] power supply

[P] Power Supply model

Option:

- ◆ SLIDE-18 18" Rackmount slide
- ◆ SLIDE-24 24" Rackmount slide
- ◆ EXTENDER-6 6"extender for 18" or 24" slide
- ◆ T-R121B 3M Micro Touch Resistive touch screen