



# Ampro CoreModule™ 600

## Celeron® PC/104-Plus Single Board Computer

Highly Integrated, High Performance, RoHS-Compliant



# CoreModule 600

### Choose Ampro CoreModule™ 600 for...

Embedded applications that need high performance in a compact size and RoHS compliance.

### Description

Ampro CoreModule™ 600 offers ultra low-power Celeron® performance with advanced networking, high-performance graphics and all of the PC-compatible component subsystems.

(Not recommended for new designs.)



- 10/100 Ethernet
- 2 Serial, 2 USB ports
- PC/104-Plus expansion

### Ordering Information

MODEL	DESCRIPTION
CM3-600-K-02	400MHz QuickStart Kit (R-02 SBC, 256MB DRAM, Cable Kit, Software, Documentation)
CM3-600-R-01	400MHz ULV Celeron® CPU, PC/104-Plus, Ethernet, Video, 2 COM, 128MB DRAM
CM3-600-R-02	400MHz ULV Celeron® CPU, PC/104-Plus, Ethernet, Video, 2 COM, 256MB DRAM
CM3-600-VV-01	Cable Kit

### Specifications

#### PROCESSOR

- 400MHz Ultra Low Voltage Celeron®
- Cache – 256kB Level 2
- Chipset – Via Twister-T
- FSB – 100MHz
- System Controllers – PC-compatible DMA and interrupt controllers and timers
- Real Time Clock – Battery-backed RTC/CMOS
- Watchdog Timer
- Powerfail Reset – Triggers when key voltage drops below predetermined threshold

#### MEMORY

- DRAM – Up to 256MB soldered SDRAM

#### BUS INTERFACE

- PC/104-Plus (ISA and PCI)

#### I/O

- EIDE – Single PCI-bus Enhanced Ultra DMA 33/66/100 Synchronous IDE interface supports up to two hard drives
- Compact Flash Socket on primary IDE
- Serial – 2 ports, one is RS232/422/485
- Parallel – EPP/ECP bidirectional port
- Floppy – Supports 1 or 2 drives, shared with parallel
- USB – 2 USB 1.1 ports (two root hubs)
- Keyboard/Mouse – PS/2 interface

#### NETWORK INTERFACE

- Ethernet – Intel 82551ER 10/100BaseT

#### VIDEO INTERFACE

- Controller – Integrated S3 Savage AGP 4X
  - DVD Multimedia Accelerator
  - Supports resolutions to 1600x1200
  - Up to 32MB UMA Frame Buffer
  - Supports TTL and STN LCDs and digital panels
  - Supports 3.3V, 5V flat panels

#### SOFTWARE

- OS Support – Linux® 2.4.18, VxWorks® v5.5, QNX® v6.3, Windows® CE 5.0, XP, XPe (See Web site for details)
- BIOS – General Software 5.2 with Ampro extensions

#### MECHANICAL

- Size – 90x96mm (3.6x3.8"); PC/104-Plus form factor
- Power Requirements – (with 128MB RAM, 100% Loaded)
  - 1.8A @ 5V
- Temperature (100 CFM system air flow)
  - Standard: –20° to +70°C
  - Optional: –40° to +85°C
  - Storage: –55° to +85°C
- Board Thickness – .093" (2.3mm)

**For more information, pricing, and details on volume discounts, please call us at 1.800.966.5200 or +1.408.360.0200.** We'll immediately connect you to your local distributor.

Don't see the product you need? Contact us at 1.800.966.5200 or +1.408.360.0200 for information about our semi-custom and custom solutions.

**Get Started Today. Order a QuickStart Kit Now.**



5215 Hellyer Ave., Ste. 110, San Jose, CA 95138 Tel. 408.360.0200 Fax 408.360.0222 sales@ampro.com

JAN.07

NOTICE: The product specifications provided in this datasheet are subject to change without notice. Every effort has been made to ensure the accuracy of this document. Ampro Computers, Inc., makes no warranties, expressed or implied, regarding errors or admissions and assumes no legal liability or responsibility for loss or damage resulting from the use of this document's information. ©2007 Ampro Computers, Inc. All rights reserved. Ampro is a registered trademark and CoreModule, LittleBoard, Little Board, ReadyBoard, ReadyBox, ReadySystem, RuffSystem, MightyBoard and MightySystem are trademarks of Ampro Computers, Inc. All other trademarks and registered trademarks are the property of their respective owners.