



## Motherboard Asus N4L-VM DH S479

Mini ATX Board for Intel Core Duo /Solo CPU's

www.ipc-markt.de



### Features

#### Mikro ATX Board with Socket 479

- 945GM/ICH7
- VGA
- USB 2.0 / Firewire
- GigaBit LAN
- SATA RAID/ eSATA / SATA II
- 7.1 Audio (ALC882M)
- 1x PCIe x 16, 1x PCIe x1
- 2x PCI

### Specification

- \* **Socket 479 for Intel Core Duo/ Solo CPU's**
- \* **RAM** Dual DDR-II 667/533 MHz, non-ECC, unbuffered (240pin DIMM)
- \* **Expansion** : 1x PCIe x16, 1x PCIe x1, 2x PCI
- \* **Graphics** : Integrated Intel GMA950
- \* **Intel ICH7 South Bridge** :  
1x UltraDMA 100/66/33, 2 x sATA  
Support Raid 0,1 and Intel Matrix Storage Technology
- \* **Audio**: Realtek ALC 882M, 8ch High-Definition Audio CODEC  
(Dolby Master Studio, Dolby Prologic IIX, Dolby Headphone,  
Dolby Virtual Speaker, Dolby Digital Live)
- \* **LAN**: Intel 82573L GB Ethernet
- \* **Rear Panel** : 1x VGA, 4x USB, 1x IEEE 1394, 1x extern sATA  
1x RJ45, 1x PS/2 Keyboard, 1x PS/2 Mouse, 1x optical S/PDIF out,  
1x Coax S/PDIF out, 1x 8 channel Audio I/O
- \* **Internal Headers** : 2x USB, 1x IEEE 1394, 1x COM, LPT<sub>r</sub>, 1x TV out,  
1 x S/PDIF in/out, 1x Game/Midi, Azalia Front Panel Audio s,  
CD Audio in
- \* **Power** : 24-pin ATX-Connector , 4pin ATX 12V Connector

**Dimensions** : : 24,5 x 24,5cm mATX

Approval : FCC, CE

**Environmental** Temperature : 0- 50 Degr. C

Shock :