



RX815ELT-LF

Intel® Pentium® III/Celeron® Micro ATX

Features

- Intel® Pentium® III / Celeron® PGA 370 Socket with 66/100/133 MHz FSB
- Intel® 82815E GMCH Chipset
- Three DIMMs up to 512 MB SDRAM Non ECC Memory
- Integrated Intel® 3D with Direct AGP, DVO
- ADI AD1885 AC'97 support 2 CH Audio
- Intel® 82562ET 10/100Mbps LAN
- 1 x AGP, 3 x PCI , 1 x CNR (Optional)
- 2 x COM, 4 x USB
- Micro ATX Form Factor (9.6" x 8.6")
- RoHS Compliant



AGP

2 COM

4 USB

3 PCI

DVO



Specifications

System

CPU	Intel® Pentium® III / Celeron® PGA 370 Socket 66/100/133 MHz FSB
Core Logic Chipsets	Intel® 82815E GMCH + Intel® 82801BA ICH2
System Memory	Three 168-pin DIMM sockets support up to 512 MB SDRAM Non ECC
BIOS	Whizpro 4 MB FWH BIOS
Expansion Interface	1 x AGP 4X/2X Slot 3 x 32-bit PCI Slot 1 x CNR Slot (Optional)
Additional Features	Power Management APM version 1.2 WOL (Wake On LAN) and WOR (Wake On Ring)

I/O

MIO	1 x K/B, 1 x Mouse, 2 x IDE, 1 x LPT
USB	2 x USB 1.1 ports (Rear I/O), 4 x USB pin header for additional 4 USB
COM Port	1 x RS232 for COM1 (Rear I/O), 1 x RS232 pin header for COM2
IrDA	1 x IrDA Tx/Rx Header

Display

Chipset	Intel® 82815E GMCH
Resolution	CRT Mode: Up to 1600 x 1200 @ 8bpp
VGA/LCD Interface	1 x DB-15 / 1 x DVO
TV-out	

Audio

AC'97 Codec	ADI AD1885 support 2 Channel Audio
Audio Interface	Line-Out, Line-In, Mic-In, CD Audio-In and Aux-In

Ethernet

LAN 1	Intel® 82562ET 100Base-Tx Fast Ethernet
-------	---

Mechanical and Environment

Power Supply Voltage	+3.3 V, +5 V, +12 V, +5 VSB, -5 V
Power Type	ATX
Operating Temperature	0° C to 60° C
Operating Humidity	-20° C to 80°
Form Factor	Micro ATX
Dimensions	9.6" (L) x 8.6" (W)
Weight	1.20 lbs

Ordering Information

Part Number	Description
RX815ELT-LF	RX815ELT RoHS replacement - Intel® 815E chipset, 1 10/100 LAN, 1 AGP, 3 PCI, 2 IDE, 2 COM, 4 USB

* All product specifications are subject to change without notice. Last update: 05/18/07