

The Innovative Solution

SAX - 906



SAX-906

- ✓ **Slim and ingenious layout**
- ✓ **Unlimited expandability and flexibility**
- ✓ **Super brilliant TFT LCD screen**

SAX-906 is one of the most demanding portable computing solutions in business applications or digital environments. Its slim and ingenious layout focuses on space saving and unsurpassed power, more than any other existing comparable systems. SAX-906 accommodates a standard size ATX motherboard to fit various technical requirements, but its expandability and flexibility are unlimited. A combination of seven slots, two 5.25" drive bays and two 3.5" drive bays, manifests the truth: SAX-906 is the innovative solution for organizations' most critical applications. A 17" super brilliant TFT LCD screen allows users to fully enjoy the beauty of true colors. The new RJ-45 cabling style fits in users' "pack-and-go" modern life style, in order to avoid unnecessary detachment of cable from the computer unit. An arch design of the handle and the fine-texture coating of flash gray also draw SAX-906 a perfect appearance.

Host Applications:

- Multimedia Creations
- Field Data Acquisition
- Portable Unix Database Servers
- Mobile Internet & Web Servers
- Customer Demos



www.acmeportable.com
info@acmeportable.com

SAX-906H Specification

Model No.	SAX-906H
Motherboard	ATX, SBC-IB840
Slot	7
Drive Bay (Vertical)	2 x 5.25" 2 x 3.5"
Color	Flash Gray
LCD	17" (Non Tiltable) LCD 280 nits brightness, 50,000 hrs of backlight life
Resolution	1280 x 1024
D/C	CB7301 ATI M6 AGP 4X 64MB ATI M6 PCI 64MB
Keyboard/Mouse	108 keys, multi-languages/touchpad, RJ-45 connector
Case Size	17.52" x 13.11" x 9.96" (445mm x 333mm x 253mm)
Power Supply	Full range PS/2 400 Watt with Active PFC
SKD Weight	11.5 kgs (25.3 lbs)
Speaker	Built-in amplified speakers Amplified board output: 2 x 6 Watt Stereo Dual Speaker output: 2 Watt
Carrying Case	Padded carrying case with wheels
Card Stabilize Bars	2
Cooling System	1 x 80mm x 80mm x 25mm (chassis fan) 1 x 120mm x 120mm x 25mm (back cover)
Case	External chassis-flame retardant ABS plastic/internal chassis-gold color aluminum alloy
Environmental Specification	
Oper. Temp.	0°C-50°C
Relative Lum.	20-80% (non-condensing)
Shock (operating, all axes)	15g
Vibration (operating, all axes)	1.25g @ 10-100Hz
Comply to	CE & FCC Class B, CCC



GSA # GS-35F-0127M / SDB # WA000017577

1330 Mountain View Circle
Azusa, CA 91702 U. S. A.
Telephone: (626) 610-1888 • Fax: (626) 610-1881
www.acmeportable.com • info@acmeportable.com

