



HS-SERIES: 32KB, METAL MOUNT ACTIVE TAGS



HS232

Size	52x103x13mm
Memory	32 KBytes
Freq. Range	300-450 KHz
Air Protocol	EMS HS
Stor. Temp	-40 to 85 C
Oper. Temp	-10 to 49 C
IP Rating	IP66
Battery Life:	200 Million bytes transferred or 10 years, whichever comes first

BATTERIES ARE NOT REPLACEABLE FOR THIS TAG.

ANTENNA / CONTROLLER COMPATIBILITY:

CHS1265-Series
HS500/A
HS501/A
CM Series

HS232R

Size	37x92x16mm
Memory	32 KBytes
Freq. Range	300-450 KHz
Air Protocol	EMS HS
Stor. Temp	-40 to 85 C
Oper. Temp	-10 to 49 C
IP Rating	IP67
Battery Life:	150 Million bytes transferred or 10 years, whichever comes first

BATTERIES ARE REPLACEABLE FOR THIS TAG.

ANTENNA / CONTROLLER COMPATIBILITY:

CHS1265-Series
HS500/A
HS501/A
CM Series

HS232LR

Size	53x102x35mm
Memory	32 KBytes
Freq. Range	300-450 KHz
Air Protocol	EMS HS
Stor. Temp	-40 to 85 C
Oper. Temp	-10 to 49 C
IP Rating	IP66
Battery Life:	200 Million bytes transferred or 10 years, whichever comes first

BATTERIES ARE REPLACEABLE FOR THIS TAG.

ANTENNA / CONTROLLER COMPATIBILITY:

CHS1265-Series
HS500/A
HS501/A
CM Series

HS232XL

Size	54x104x22mm
Memory	32 KBytes
Freq. Range	300-450 KHz
Air Protocol	EMS HS
Stor. Temp	-40 to 85 C
Oper. Temp	-40 to 85 C
IP Rating	IP66
Battery Life:	800 Million bytes transferred or 10 years, whichever comes first

BATTERIES ARE NOT REPLACEABLE FOR THIS TAG.

ANTENNA / CONTROLLER COMPATIBILITY:

CHS1265-Series
HS500A
HS501/A
CM Series