

Industrial PC Platform



Entry Level Rackmount PICMG Pentium 4 Solution

R4AB-975

**4U Rackmount PICMG Pentium 4 Platform
with 400 MHz FSB, PC133 SDRAM/ECC
4xAGP SVGA/32 MB VRAM, Dual LAN, IDE RAID
External 3 x 5.25" and 1 x 3.5" Drive Bay
Free 12 PCI/ISA Expansive Slots and ISA High Drive**



Industrial PC Platform

Form Factor	4U 19" Rackmount EIA RS-310C industrial PC chassis PICMG version 1.0 (Rev. 2.0) and PCI version 2.0 compliant
CPU Card (SBC)	COMMELL FS-975 PICMG Socket 478 Pentium 4 Single Board Computer Based on Intel 845 MCH and ICH2 chipset
CPU	Intel Socket 478 Pentium 4 / Celeron CPU up to 2.8 GHz @ 400 MHz FSB Intel 0.13- / 0.18-micron Northwood / Willamette Pentium 4 / Celeron CPU
Memory	Three 168-pin DIMM sockets support 3 GB PC133 SDRAM with ECC (No-registered)
Watchdog Timer	Generates NMI or system reset with 1 to 255 sec. / min. of time out value
Power Management	ACPI 1.0 compliant, supports power saving mode with ATX power supply
Solid State Disk	M-systems 32-pin DIP JEDEC DiskOnChip socket up to 1 GBytes of capacity IDE-based DOM (DiskOnModule) or M-systems DiskOnChip IDE Pro on IDE port
PCI Enhanced IDE	Dual UltraATA/100 bus master IDE channels up to 4 ATAPI devices Jumper selectable +5V Vcc on IDE2 for power cable free DOM (DiskOnModule)
VGA Interface	Onboard 4xAGP SiS315 VGA controller with 256-bit 3D engine Onboard 32 MBytes independent video memory
LAN Interface	Onboard dual Intel PRO/100+ LAN interfaces, IEEE 802.3U compliant 1st LAN with Intel ICH2 and 82562ET, optional 2nd LAN with Intel 82559ER
RAID Interface (Optional)	Promise FastTrak100 UltraATA/100 IDE RAID with PCI PDC20265R controller Support RAID level 0 striping and level 1 mirroring Onboard dual 40-pin IDE ports (IDE3/4) for RAID-based HDD
Multi-I/O Port	2 x RS-232 serial ports (1 jumper selectable RS-232/422/485 serial port) 1 x SPP/EPP/ECP parallel port, 2 x USB 1.1 ports IrDA port, floppy port, AT keyboard, PS/2 keyboard and mouse port
Drive Bay	External 3 x 5.25" and 1 x 3.5" drive bay, internal 1 x 3.5" drive bay All with advanced shock / vibration proof construction
Expansive Interface	12 x PCI / ISA expansive bus interface with PICMG industrial passive / active backplane Optional free 4 x PCI / 8 x ISA, 7 x PCI / 5 x ISA, 12 x PCI and 12 x ISA expansive slots Intel PCI bridge for multiple PCI and ISA 64mA high drive for multiple ISA platform Free 8 x full-size and 4 x half-size add-on cards with hold-down clamp
Thermal Control	One dual ball-bearing 12cm / 85 CFM system cooling fan on the front panel Removable air / dust filter on the external front panel
Front Panel	Lockable front door for system safety, security and dust-proof Power / access LED, power / reset switch and AT keyboard connector