

CMI110



Features

- Mini-ITX system supports IBASE DC-in motherboards (MI920, MB890 & MB500)
- Expandable for various applications
- Available in black color
- One 2.5" HDD drive bay
- Medium box design with 1x 5cm fan (optional)
- Wall mount kit included

Specifications

System Mainboard	MI920 / MB500
Construction	SECC
Chassis Color	Black
I/O Connectors	2x front USB, 1x front Power On/Off button, rear side I/O according to motherboard specifications
Expansion Slots	1x PCI slot
Storage	1x 2.5" HDD drive bay
Power Supply	60W power adaptor
Mounting	Desktop or wall mount
Dimensions	202mm(W) x 200mm(D) x 111mm(H)

Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CMI110-500C	Chassis for MB500 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
CMI110-890C	Chassis for MB890 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
CMI110-920C	Chassis for MI920 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
MI920EL-C6K	Intel® Celeron® M, 910GML Mini-ITX motherboard w/ VGA, DVI and 10/100
MI920EF	Socket 479 for Pentium® M/Celeron® M, 915GME Mini-ITX motherboard w/ VGA, DVI, Mini PCI-E, LVDS, 10/100 and PCI-E Gigabit LAN
MB500-R	AMD Geode LX700, 433MHz, CS5536 Mini-ITX motherboard w/ VGA and 10/100 LAN
MB500F-R	AMD Geode LX800, 500MHz, CS5536 Mini-ITX motherboard w/ VGA and dual 10/100 LAN



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.

