

# EBS 1569PS

VIA C3 w/ Audio/ PCI Expansion/ LAN x2  
Compact Embedded System



## Features

- ◆ On-board VIA C3 1GHz / 800MHz/ Eden 667MHz processor
- ◆ 168-pin DIMMx1, support Max 512MB SDRAM
- ◆ Support 2 internal 2.5" HDD devices
- ◆ 32-bit PCI
- ◆ Built-in 4 COM(Serial) ports
- ◆ On-board Compact Flash socket
- ◆ Built-in 2 speakers
- ◆ Passive heatsink for VIA Eden fanless solution

## Specifications

### Construction

- ◆ Heavy-duty steel

### Dimension

- ◆ 300(W) x 55.8 (H) x 228.6 (D) mm
- ◆ 11.8"(W) x 2.2"(H) x 9.0"(D)

### Color

- ◆ PANTONE 295U

### Main Board

- ◆ EBC 569/ EBC 569LP6

### Device

- ◆ 168-pin DIMMx1, support Max 512MB SDRAM
- ◆ Internal 2.5" HDD Drive Bayx2

### I/O ports

- ◆ 10/100 Fast Ethernet LAN port x2
- ◆ VGA port x 1
- ◆ PS/2 Keyboard/Mouse x 1
- ◆ Serial port x 4
- ◆ Speaker-out x 1; MIC-in x 1

### LED indicators

- ◆ Power-on/-off LED x1
- ◆ HDD access LED x1

### Power Module

- ◆ Power input: 90-264Vac 47/63, 2A Max
- ◆ 65W Open frame power supply

### Cooling system

- ◆ 4 cm fan for system cooling x1
- ◆ Passive heatsink for LP6 fanless series

### Environment

- ◆ Operating temperatures: 0°C to 40°C
- ◆ Storage temperatures: -20°C to 80°C
- ◆ Relative humidity: 10% to 90% (Non-condensing)

### Certification:

- ◆ CE
- ◆ FCC

## Ordering Information

Model Name	MainBoard	Chassis	65W Open frame Power Supply	EBK PCI1
EBS 1569PS	EBC 569	Yes	Yes	Yes
EBS 1569PS-LP6	EBC 569LP6	Yes	Yes	Yes

