

# CPC-1502

## 15" LCD Pentium M Panel PC

### Feature

- Front panel NEMA4 / IP 65 rating (Panel-mount)
- Resistive touch screen (optional)
- 15" SVGA(1024 x 768), 400cd/m<sup>2</sup> high-bright LCD
- VESA ARM
- Giga LAN port, 2 x USB2.0
- 2 x PCI Slot



### Specifications

CPU Support: Intel Pentium M / Celeron M processor

CPU Frequency: 1.3 - 2.0GHz

Chipset: Intel 855GME + ICH4 (FSB:400MHz)

DRAM: 1 x DDR333 SO-DIMM SDRAM upto 1GB

Watchdog: 1 - 255 secs watchdog timer selectable w/Reset/NMI

Serial Port: 2 x COM ports, COM1 for RS-232, COM2 for RS-232/422/485

LAN 1: Intel 82562EM (10/100Mbps)

LAN 2: Intel 82540EM (10/100/1000Mbps)

Support wake-on-LAN with ATX power

USB: 2 x USB2.0

Display: Built-in Intel 855GME, share system memory

HDD: 1 x 2.5" HDD

Expansion Slots: 2 x PCI Slot

Touch Screen: Resistive (optional)

Chassis: Heavy-duty steel, NEMA4/IP-65 rating panel

Mounting: Panel Mount

Shock: 10G acceleration peak to peak (11ms)

Vibration: 5 - 17Hz, 0.1" double amplitude displacement.

17 - 640Hz, 1.5G acceleration peak to peak

Power Supply: Universal AC input 220W ATX PSU

Dimensions: 410(W) x 115(D) x 310mm(H)

Weight: 7.2Kgs

