

ViewSonic® VX715 LCD Display

17" OPTISYNC SLIM BEZEL DISPLAY



Brilliant color in a versatile, stylish display.

The 17" ViewSonic VX715 LCD display is an ultra-stylish, flexible LCD at a price that fits any budget. The extended neck design provides improved ergonomics for more comfortable viewing. OptiSync® technology offers **ADDED VERSATILITY AND CONNECTIVITY** with dual digital and analog inputs to extend the desktop experience. Ultra-high brightness of 300 nits (typ) and a 450:1 (typ) contrast ratio deliver **CRISP, DETAILED IMAGES IN RICH, VIVID COLORS**. The slim bezel saves valuable desktop real estate while the integrated power supply reduces clutter.

ClearMotiv™ broadcast quality video performance, wide viewing angles and competitive pricing make the VX715 the perfect choice for small spaces and tight budgets.

Award-Winning Company

ViewSonic is the #1 best-selling monitor brand in the USA, delivering price and performance leadership.*



Quality, versatility and connectivity.

...❖ **OPTISYNC** digital/analog inputs expand your connectivity

Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.

...❖ **ClearMotiv™** technology

Super-fast 16ms video response delivers broadcast-quality full motion video at 62.5 fps.

...❖ **Stylish slim-bezel design**

The full 17" viewable screen in a thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.

...❖ **Ultra-high brightness and contrast**

300-nit brightness (typ) and 450:1 contrast ratio (typ) for rich, detailed images.

...❖ **Full 17" viewable**

...❖ **1280x1024 resolution**

...❖ **OnView® controls for superior screen adjustability**

Screen adjustments are precisely made via an easy-to-use on-screen menu.

...❖ **VESA® 100mm wall mount compliant**

...❖ **PC and Mac® compatible**

...❖ **TCO'99 and ENERGY qualified**



Create a Total Desktop Solution
Add ViewMate® Collection accessories to your display for a complete desktop solution. Choose stylish mice and wireless keyboards, or turn that display into a TV with a TV/video processor.

Cutting Edge

ViewSonic® 

the choice of professionals

ViewSonic® VX715 LCD Display

17" OPTISYNC SLIM BEZEL DISPLAY



1

2



3

4

1. Sleek buttons control all major functions
2. Extended neck, floating head design
3. Space-saving slim-line panel design is only 2.4" thick
4. Compact, attractive styling



Available colors:
Black & silver

17" COLOR LCD DISPLAY WITH ULTRA-HIGH BRIGHTNESS


LCD	Type	17" Color TFT active matrix SXGA LCD
	Display Area	13.3" horizontal x 10.6" vertical; 17.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	450:1 (typ)
	Viewing Angles	170° horizontal, 170° vertical @ contrast ratio > 5
	Response Time	16ms (typ)
INPUT SIGNAL	Video	RGB analog (75 ohms, 0.7 Vp-p); DVI-D (TMDS, 100 ohms)
	Sync	H/V separated (TTL), composite, sync-on-green
	Frequency	F _H :24–82kHz, F _V :50–85Hz
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac®**	Power Mac™ G3/G4 1280x1024
CONNECTOR	Signal	15-pin mini D-sub and DVI-D
	Power	3-pin AC plug, (CEE22)
POWER	Voltage	AC 100–240V, 50–60Hz (auto switch)
	Consumption	35W (max)
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, ViewMatch® color adjust (SRGB, 9300K, 6500K (default), 5400, user color RGB), input select (analog, digital), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness, setup menu), language (English, French, German, Italian, Spanish, Finnish, Japanese, Traditional Chinese, Simplified Chinese), resolution notice, OSD position, OSD timeout, OSD background, memory recall
OPERATING CONDITIONS	Temperature	32–104°F (0–40°C)
	Humidity	20–90% (no condensing)
DIMENSIONS (W x H x D)	Physical	388mm x 438mm x 176mm (with stand)
		15.3" x 17.2" x 6.9" (with stand)
		388mm x 332mm x 61mm (without stand)
		15.3" x 13.1" x 2.4" (without stand)
WEIGHT	Net	11.0 lb. (5.0 kg) (with stand)
	Gross	16.8 lb. (7.6 kg) (with stand)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), TCO'99, GOST-R + 20 original copies hygienic, (SASO), PCBC, VCCI, BSMI, CCC, (PSB), (C-TICK), Argentina-S, Green Mark
POWER MANAGEMENT		Meets TCO'99 and ENERGY standards
PACKAGE CONTENTS		LCD display, power cable, Quick Start Guide, ViewSonic Wizard CD, 15-pin VGA cable
WARRANTY		Three-year limited warranty on parts, labor and backlight



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic® 
the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*Leading stand-alone, branded monitor by sales (CRT and LCDs combined: iSupply/Stanford Resources Monittrak® and Flat Panel Monittrak® 4Q04 Report) **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. [12292-00B-01/05] VX715-1

For more product information, visit us on the web at ViewSonic.com

specifications