



Features

- Supports Intel® Pentium® processor with MMX™ technology and AMD K6-3
- C&T 69000 LCD controller
- Supports 36-bit TFT Panels
- One 10/100Base-T Fast Ethernet
- Supports DiskOnChip® up to 1GB
- PC/104 expansion connector



Specifications

System

- CPU** □ Socket 7 Pentium® processor with MMX™ technology
- 166- 266MHz, AMD K6-2/K6-3 266-450MHz (with system bus frequencies of 66/100MHz)
- System Memory** □ SDRAM DIMM x 1, Max. 256MB
- 2nd Cache Memory** □ Onboard 512KB pipeline burst L2 Cache
- Chipset** □ ALi 1541/1543
- I/O Chipset** □ Winbond W83977EF. Fully 16-bit I/O decoded
- BIOS** □ Award 256KB FLASH BIOS
- Ethernet** □ Realtek RTL8139X,
- 10/100Base-T RJ-45 connector x 1
- SSD** □ Supports DiskOnChip® up to 1GB
- Watchdog Timer** □ Can generate a system reset, IRQ15 or NMI
- Expansion Interface** □ ISA interface, PC/104 connector x 1
- Battery** □ Lithium battery
- DMA** □ 7 DMA channels (8237 equivalent)
- Interrupt** □ 15 interrupt levels (8259 equivalent)
- H/W Status Monitoring** □ Winbond W83781D supports power supply voltages, □ CPU fan rotation and temperature monitoring
- Power Supply Voltage** □ +5V (4.75V to 5.25V), +12V (11.4V to 12.6V), AT
- Size/ Weight** □ 7.3" (L) x 4.8" (W) (185 mm x 122 mm), 0.66lb. (0.3Kg)
- Operating Temperature** □ 32°F to 140°F (0°C to 60°C)

I/O

- MIO** □ IDE (UDMA33) x 1, FDD x 1, KB+Mouse x 1, RS-232 x 1, RS-232/422/485 x 1, Parallel x 1
- IrDA □ One IrDA Tx / Rx header
- USB** □ One 5x2 pin header supports 2 USB 1.1 port

Display

- Chip** □ C&T 69000
- Memory Size** □ Built-in 2MB SDRAM
- Resolution** □ 1024 x 768@ 16bpp colors
- LCD Interface** □ 36-bit TFT/DSTN/MONO LCD panel

Packing List

- IDE Cable □ 1701440500
- FDD Cable □ 1701340600
- COM Port Cable Kit (1parallel, 1 serial)** □ 1701010302
- KB/Mouse Cable □ 1700060191
- Quick Installation Guide Utility CD**