



- A : MATERIAL
1. PIN : BRONZE
 2. INSULATION : P.C.(or NYLON)
 3. SHELL : BRONZE, NICKEL PLATED.
 4. CON : A.B.S.
 5. COVER : PVC.

B : ELECTRICAL

RATING : 100V AC / 1 A MAX.
 INSULATION RESISTANCE : 50M OHM / 500V DC
 DIELECTRIC : 500V AC / 1 MINUTE
 CONTACT RESISTANCE : 30M OHM MAX.

| ARRANGEMENT OF CONTACTS | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-------------------------|---|---|---|---|---|---|---|---|
| NO. OF CONTACTS | 3 | 4 | 5 | 6 | 7 | 8 | | |

<FRONT VIEW>

SINGATRON ENT. CO., LTD.

| REVISION LIST | | TOLERANCE : | | APPROVED BY | | SCALE | | TITLE : | | DWG. NO. | | REV. | |
|---------------|------------------------|-------------|-------|-------------|----------|-------|------|---------|----------------------|----------|---|-------|----|
| REV | DESCRIPTION | DATE | .XX = | .XXX = | | | NONE | UNIT | P/N : | 30014 | A | SHEET | OF |
| A | INITIAL RELEASE OF DWG | FEB 02,96 | | | | | | mm | FEMALE MINI DIN PLUG | | | 1 | 1 |
| | | | | | CHECK BY | | | | | | | | |