

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506

www.ikey.com

uHP-2020

OEM HulaPoint™ Industrial Pointing Device

The uHP-2020 is a small version of the HulaPoint™ pointing device that features I eft-, right- and middle-click buttons. Its compact size ensures easy integration into various applications. Like all of iKey's products, the sealed design means the uHP-2020 is designed to be dustproof, waterproof and non-corrosive.



Technical Specifications

Certifications NEMA 4X, CE UL60950, FCC Part 15 Class B

Shock 3 x 11 ms pulses of 50g on each of 3 axis

Cable LENGTH: 6' (1.8 m)

Key Switch MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.040 in. ACTUATION FORCE:

200g FEEDBACK: Tactile with Mechanical Snap

Vibration POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3

hours

Power PS/2: POINTER: 15mA@5V (from Mouse port) STANDARD: POINTER: 15mA@5V (from Serial port)

Compatability PS/2: All Windows Operating Systems STANDARD: All Windows Operating Systems

Temperature Range STORAGE: -40C to +90C OPERATING: -40C to +70C

Weight 0.25 lbs (0.11 kg)

Warranty 90 day limited warranty

Humidity 100% Humidity Resistant

Dimensions 1.80" x 1.90" x 0.98" (w-h-d) 45.7mm x 48.3mm x 24.9mm

Features and Benefits

• AT/Serial and PS/2 configurations available

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800- 866-6506