Noritake itron

GU112X16G-7900

SIMPLIFIED DATASHEET

■ Features

The most compact VFD module in the GU-7000 series.
Size compatible with typical LCD modules, for flexible positioning, or as drop-in replacement.

Get full specification

Click here to go to request form.

■ Physical dimension



Specifications

■ Electrical Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Power supply voltage	VCC	4.75	5.00	5.25	VDC	-

■ Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
'L' Logic Input Current						
D0-D7,/WR,/RD	IIL1	-	-	-0.15	mA	VIN=0V
/RESET	IIL2	-	-	-0.6	mA	VIN=0V
'H' Logic Input Current						
D0-D7,/WR,/RD,/RESET	IIH	-	-	1.0	μADC	VIN=5V
Logic Input Voltage	VIH	0.8VCC	-	VCC	VDC	-
D0-D7,/WR,/RD,/RESET	VIL	0	-	0.2VCC	VDC	-
Logic Output Voltage	VOH	3.8	-	VCC	VDC	IOH=-1.5mA
D7(Busy flag), PBUSY	VOL	0	-	0.6	VDC	IOL=1.6mA
Logic input resistance						
SIN	RIN	3	-	-	KΩ	-
Logic Input Voltage	VIH	3.0	-	+15	VDC	-
SIN	VIL	-15	-	0.5	VDC	-
Logic Output Voltage	VOH	4.0	-	VCC	VDC	RL=3KΩ
SBUSY	VOL	0	-	0.5	VDC	RL=3KΩ
Power Supply Current 1	ICC-1	-	260	340	mADC	All dots ON
Power Supply Current 2	ICC-2	-	220	290	mADC	All dots OFF
Power Supply Current 3	ICC-3	-	35	45	mADC	Display power OFF
Power Consumption		-	1.3	1.7	W	All dots ON

■ Optical Specifications

Parameter	
Number of Dots	1,792 (112 x 16)
Character numbers	16 x 2 / Max18 x 2 by 5 x 7 dot ANK 7 x 1 by 16 x 16 dot 2-byte character
Display Area	52.5 mm x 11.45 mm
Dot Size (X x Y)	0.33 mm x 0.575 mm
Dot Pitch (X x Y)	0.47 mm x 0.725 mm
Luminance	350 cd/m^2 Min. (700 cd/m^2 Typ.)
Color of illumination	Green (Blue-Green)

■ Environmental Specifications

Parameter	
Operating Temperature	-40 ~ +85 degrees celsius
Storage Temperature	-40 ~ +85 degrees celsius
Operating Humidity	20 ~ 80% R.H. (non-condensing)
Storage Humidity	20 ~ 80% R.H. (non-condensing)
Vibration (non-operating)	10-55-10Hz, all amplitude 1mm, 30 minutes, X-Y-Z
Shock (non-operating)	392m/s^2 (40G) 9ms X-Y-Z, 3 times each direction

■ Character display

Parameter		
Number of Dots	112 x 16 dots	
Character font type	5 x 7	ANK, International font
	8 x 16	ANK, International font
	16 x 16	2-byte character
Character width	Fixed/Proportional character format 1&2	
Attribution	Character magnify, Reverse	
Weight	About 31 g	

■ Interface

Parallel(CMOS), Asynchronous Serial (RS232)

■ Pin Assignment (Parallel)

Pin No.	Signal	Pin No.	Signal
1	GND	8	D1
2	Vcc	9	D2
3	NC	10	D3
4	RS	11	D4
5	/WR	12	D5
6	/RD	13	D6
7	D0	14	D7(PBUSY)

(Asynchronous Serial)

Pin No.	Signal
1	Vcc
2	SIN
3	GND
4	SBUSY
5	NC
6	/RESET

Baud Rate Setting
9600bps
19200bps
38400bps*
115200bps
(*:Default setting)

■ Functions

Parameter
Control command
Scroll display action
Proportional Font function
User-Windows function
AND/OR/XOR Mixture display
Reverse display
Bit image display
FROM bit image definition
Character download function
etc.

RoHS COMPLIANT

Leaflet contents, and specifications and external appearance of products, may change without notice.
Please confirm product details in the specification.
(C)Copyright NORITAKE ITRON CORP.