

SPECIFICATIONS

Model	5 tiers	WE – 502					
	4 tiers	WE – 402					
	3 tiers	WE – 302					
	2 tiers						
	1 tier						
Rated Voltage		24V AC/DC (50/60Hz)					
Operating Voltage		Rated Voltage ±10%					
Current Consumption	Per Unit	Red	Amber	Green	Blue	White	Buzzer
		Typ.	24.0mA		17.0mA		
		Max.	28.0mA	27.0mA	23.0mA		
Operating Temperature Range (Relative Humidity)		- 30°C to + 60°C (Less than 90%)					
Mounting	Location	Indoor Only					
	Direction	Upright, Inverted & Sideways					
Protection Rating		IP 65					
Vibration Resistance		19.6m / s ² (30Hz, Back and Forth:2h · Right to Left:2h · Up and Down:2h)					
Insulation Resistance		More than 1MΩ at 500VDC between the terminals and the chassis					
Withstanding Voltage		500VAC applied for 1min between terminals and chassis without breaking insulation					
Flashing Rate							
Buzzer	Sound Level						
	Tone						
Luminous Intensity	Red	Amber	Green	Blue	White		
	600mcd	800mcd	2000mcd	600mcd	1800mcd		
Mass (Tolerance ±10%)	1 tier	2 tiers	3 tiers	4 tiers	5 tiers		
			0.3kg	0.33kg	0.35kg		
No.WE-502-PDFA-EN-1_2							
<ul style="list-style-type: none"> ● Cover Surface: Chromium Plating ● This product conforms to the CE requirements and shows the CE Marking. ● Recognized as a UL standard. (Standard No. UL508, File No. E215660) ● This product complies with the RoHS Directive (DIRECTIVE 2002/95/EC) 							
PATLITE Corporation							