

ACE-T140A

400 W PS/2 Type AT Power Supply

400W



Specifications

Input Type	95~264VAC Full Range			
Output Voltage	+5 V	+12 V	-5 V	-12 V
	42.0 A (2.0 A min.)	15 A (1.0 A min.)	0.3 A (0 A min.)	0.8 A (0 A min.)
Efficiency	75 %			
Temperature	Operating: 0 °C~50 °C, Storage: -20 °C~80 °C			
MTBF	50,000 hr			
Output Connector	p8+p9 x 1, HDD x 6, FDD x 2			
Dimensions	140 mm x 150 mm x 86 mm			

Ordering Information

Part No.	Description
ACE-T140A-RS	400 W AC-DC PS/2 2U AT Power Supply, with PFC

ACE-925AP-U

250 W PS/2 Type AT Power Supply

250W

High reliability magnetic bearing cooling system Features low noise, high Op temperature and longer MTBF



Specifications

Input	Voltage	90 ~ 265 VAC Full Range			
	Frequency	47 ~ 63 Hz			
Output	Voltage	+5 V	+12 V	-5 V	-12 V
	Max. load	22 A	11 A	0.5 A	0.7 A
General	MTBF	100,000 hours			
	Temperature	Operating : 0 °C ~50 °C Storage : -25 °C ~ 70 °C			
	Dimensions	140 x 150 x 86 (mm)			
	Output Connector	P8+P9x1, FDDx2, HDD/CDROMx4, SATAx2			

Ordering Information

Part No.	Description
ACE-925AP-U-RS	250 W AC-DC PS/2 AT Power Supply, with PFC

ACE-935AL

300 W PS/2 Type AT Power Supply

300W



Specifications

Input Type	85 ~ 140 VAC, 170 ~ 270 VAC Auto Range					
Output Voltage	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
		40 A (3A min)	8 A (0.1A min)	0.3 A	0.7 A	
Efficiency	68 %					
Temperature	0 °C ~ 50 °C (Operating), -40 °C ~ 75 °C(Storage)					
MTBF(hrs)	100,000					
Output Connector	P8+P9 x1, Extra +5V(P10) x1, HDD/CDROM x5, FDD x2					

Ordering Information

Part No.	Description
ACE-935AL-RS	300 W AC-DC PS/2 AT Power Supply, AC select switch

ACE-925AP-V20