



PE-3S

- ◆ PICMG1.3 half-size slot x 1
- ◆ PCI slot x 2
- ◆ ATX/Fan power connector
- ◆ PCI Bridge controller
- ◆ 175.0(L) x 78.0(W) mm

PE-3S1

- ◆ PICMG1.3 half-size slot x 1
- ◆ PCIex1 slot x 1
- ◆ PCIex16 slot x 1
- ◆ ATX/Fan power connector
- ◆ 175.26(L) x 78.0(W) mm

PE-3S2

- ◆ PICMG1.3 half-size slot x 1
- ◆ PCIex4 slot x 1 (but x1 PCEe signal)
- ◆ PCIex16 slot x 1
- ◆ ATX/Fan power connector
- ◆ 175.26(L) x 108.0(W) mm



PE-4S

- ◆ PICMG1.3 half-size slot x 1
- ◆ PCIex1 slot x 1
- ◆ PCI slot x 2
- ◆ ATX/Fan power connector
- ◆ PCI Bridge controller
- ◆ 175.0(L) x 98.0(W) mm

PE-4S1

- ◆ PICMG1.3 half-size slot x 1
- ◆ PCIex16 slot x 1
- ◆ PCI slot x 2
- ◆ ATX/Fan power connector
- ◆ PCI Bridge controller
- ◆ 175.26(L) x 98.43(W) mm

PE-4S2

- ◆ PICMG1.3 half-size slot x 1
- ◆ PCIex16 slot x 1
- ◆ PCI slot x 2
- ◆ ATX/Fan power connector
- ◆ PCI Bridge controller (PEX 8111)
- ◆ 175.26(L) x 98.43(W) mm



PE-6S

- ◆ PICMG1.3 half-size slot x 1
- ◆ PCIex1 slot x 1
- ◆ PCI slot x 4
- ◆ ATX/Fan power connector
- ◆ PCI Bridge controller
- ◆ 175.0(L) x 128.5(W) mm

PCIE-5SD

- ◆ PICMG1.3 full-size slot x 1
- ◆ PCIex1 slot x 1
- ◆ PCIex16 slot x 1
- ◆ PCI slot x 2
- ◆ SATA port x 2
- ◆ ATX/Fan power connector
- ◆ Double-sided
- ◆ 327.64(L) x 79.51(W) mm

PCIE-14S

- ◆ PICMG1.3 full-size slot x 1
- ◆ PCIex4 slot x 2 (x1 signal)
- ◆ PCIex16 slot x 1
- ◆ PCI slot x 10
- ◆ ATX/Fan power connector
- ◆ Dual PCI Bridge controller
- ◆ 327.66(L) x 302.26(W) mm