



WD RE4

Enterprise SATA Hard Drives

Ideal for servers, video surveillance, and other demanding write-intensive applications, WD RE4 7200 RPM Enterprise SATA hard drives offer up to 2 TB capacity, 64 MB cache, 4th generation vibration tolerance and 5-year limited warranty.



INTERFACE

SATA 3 Gb/s

WIDTH/HEIGHT

3.5-inch/1-inch

ROTATIONAL SPEED

7200 RPM

CAPACITIES

250 GB to 2 TB

MODEL NUMBERS

WD2003FYYS WD5003ABYX
WD1003FBYX WD2503ABYX

Note: Not all products may be available in all regions of the world.

Product Benefits

Massive capacity

WD RE4 Enterprise SATA drives are available with up to 2 TB of cavernous capacity.

Dual processor

With double the processing power, WD RE4 boasts the highest performance of any drive in the WD RE family.

RAFF™

Enhanced RAFF technology includes sophisticated electronics to monitor the drive and correct both linear and rotational vibration in real time. The result is a significant performance improvement in high vibration environments over the previous generation of drives.

Dual actuator technology

A head positioning system with two actuators that improves positional accuracy over the data track(s). The primary actuator provides coarse displacement using conventional electromagnetic actuator principles. The secondary actuator uses piezoelectric motion to fine tune the head positioning to a higher degree of accuracy. (2 TB only)

StableTrac™

The motor shaft is secured at both ends to reduce system-induced vibration and stabilize platters for accurate tracking during read and write operations. (1 TB and larger drives only)

IntelliSeek™

Calculates optimum seek speeds to lower power consumption, noise, and vibration.

Multi-axis shock sensor

Automatically detects the subtlest shock events and compensates to protect the data.

RAID-specific, time-limited error recovery (TLER)

Prevents drive fallout caused by the extended hard drive error-recovery processes common to desktop drives.

NoTouch™ ramp load technology

The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit.

Thermal extended burn-in test

Each drive is put through extended burn-in testing with thermal cycling to ensure reliable operation.

Third generation dynamic fly height

Each read-write head's fly height is adjusted in real time for optimum reliability.

24x7 reliability

With 1.2 million hours MTBF (tested at 100% duty cycle), these drives have the highest available reliability rating on a high-capacity drive.

Applications

Ideal for servers, storage arrays, video surveillance, and other demanding applications.

PUT YOUR LIFE ON IT®



WD RE4

Specifications ¹	2 TB	1 TB	500 GB	250 GB
Model number	WD2003FYYS	WD1003FBYX	WD5003ABYX	WD2503ABYX
Interface	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s
Formatted capacity	2 TB	1 TB	500 GB	251 GB
User sectors per drive	3,907,029,168	1,953,525,168	976,773,168	490,350,672
Native command queuing	Yes	Yes	Yes	Yes
SATA latching connector	Yes	Yes	Yes	Yes
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Performance				
Data transfer rate (max)				
Buffer to host	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s
Host to/from drive (sustained)	138 MB/s	128 MB/s	128 MB/s	128 MB/s
Cache (MB)	64	64	64	64
Rotational speed (RPM)	7200	7200	7200	7200
Average drive ready time (sec)	21	18	14	14
Configuration/Organization				
Heads/disks	8/4	4/2	2/1	1/1
Bytes per sector (STD)	512	512	512	512
Reliability/Data Integrity				
Load/unload cycles ²	600,000	600,000	600,000	600,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
Limited warranty (years) ³	5	5	5	5
Power Management				
12VDC (A, max)	1.8	1.6	2.25	2.25
Average power requirements (W)				
Read/Write	10.7	7.9	6.4	6.4
Idle	8.2	5.9	4.5	4.5
Standby	1.3	0.7	0.8	0.8
Sleep	1.3	0.7	0.8	0.8
Environmental Specifications⁴				
Temperature (°C)				
Operating	5 to 55	5 to 55	5 to 55	5 to 55
Non-operating	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock (Gs)				
Operating (2 ms, read/write)	30	30	30	30
Operating (2 ms, read)	65	65	65	65
Non-operating (2 ms)	300	300	350	350
Average acoustics (dBA) ⁵				
Idle mode	29	28	27	27
Performance seek mode	34	33	30	30
Quiet seek mode	30	29	29	29
Physical Dimensions				
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.66/0.75	1.49/0.68	0.99/0.45	0.99/0.45

¹ As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

² Controlled unload at ambient condition

³ The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

⁴ No non-recoverable errors during operating tests or after non-operating tests.


⁵ Sound power level.

Western Digital
3355 Michelson Drive, Suite 100
Irvine, California 92612
U.S.A.

For service and literature:

<http://support.wdc.com>
www.westerndigital.com

800.ASK.4WDC North America
800.832.4778 Spanish
+800.6008.6008 Asia Pacific
00800.27549338 Europe
(toll free where available)
+31.880062100 Europe/Middle East/Africa



Canada ICES-003 Class B / NMB-003 Classe B

Western Digital, WD, the WD logo, and Put Your Life On It are registered trademarks in the U.S. and other countries; and NoTouch, IntelliSeek, StableTrac, RAFF, and FIT Lab are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.