

DF6AB10

fuse holder - DF6 - 1P - 32 A - for fuse NFC 10 x 38 mm



Main

Range of product	DF6
Device short name	DF6 AB
Fuse size	8.5 x 31.5 mm 10 x 38 mm
Product or component type	Fuse holder
Poles description	1P
Network type	AC DC
[I _{th}] conventional free air thermal current	25 A at ≤ 40 °C with aM cartridge fuses 30 A at ≤ 40 °C with gG cartridge fuses 32 A at ≤ 40 °C with tubular links
Quantity per set	Set of 12

Complementary

Network frequency	50/60 Hz
Mounting support	Rail
[U _i] rated insulation voltage	690 V
[I _{pk}] rated peak withstand current	8 kA with tubular links conforming to IEC 60269-1
Connections - terminals	Control circuit: screw terminals 1 cable 10 mm ² - cable stiffness: flexible - without cable end Control circuit: screw terminals 2 cable 6 mm ² - cable stiffness: flexible - without cable end Control circuit: screw terminals 1 cable 10 mm ² - cable stiffness: solid - without cable end Control circuit: screw terminals 2 cable 6 mm ² - cable stiffness: solid - without cable end
Tightening torque	Control circuit: 1.2 N.m - on screw terminals
Operating position	+/- 23°
Height	81 mm
Width	17.5 mm
Depth	68 mm
Product weight	0.07 kg

Environment

Standards	IEC 60947-3 NF C 61-201
Protective treatment	TC
Ambient air temperature for operation	-50...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.