

# Bases & Mounts

## Rooftop Mounts

### Quarter-wave Mount

#### Model K-44

Complete 3/8 inch (9.5 mm) diameter hole snap-in mount for quarter-wave rooftop (ASP-201) models. Includes K-45. Cable and connector not supplied.



### Toggle Mount

#### Model K-49

3/4 inch (19.1 mm) toggle mount for standard loaded antennas. Cable and connector not supplied.



### Snap-in Mount Adapter

#### Model K-45

Replacement 3/8 inch (9.5 mm) diameter hole snap-in mount adapter only for rooftop mounts.



### 3/4 Inch Mount Adapter

#### Model K-145

3/4 inch (19.1 mm) diameter hole replacement mount kit. Replacement for K-45 where mounting hole has been damaged.



### Snap-in Mount

#### Model K-57

3/8 inch (9.5 mm) snap-in mount for standard loaded antennas. Cable and connector not supplied.



### Low Profile Antenna Mounts

#### Model K-66

Replacement 3/4 inch (19.1 mm) diameter hole mount and cable assembly for A/S low profile antennas. Furnished with 17 ft (5.2 m) of RG-58/U cable, PL-259 connector and spanner wrench for quick installation.



#### Model KD66

Deluxe replacement 3/4 inch (19.1 mm) diameter hole mount for A/S low profile antennas. Furnished with 17 ft (5.2 m) of PRO-FLEX cable, PL-259 connector and spanner wrench.

*Mosaic*<sup>®</sup>

### Motorola Style Mounts

#### Model KRM66

Similar to K-66 except Motorola style mount and 14 ft (4.3 m) of RG-58/U cable and PL-259 connector.

#### Model KRMX66

Similar to K-66 except Motorola style mount and 17 ft (5.2 m) of RG-58/U for ASP-7450 and ASP-7650 series. Connector available separately.

#### Model KREMX66

Similar to K-66 except Motorola style mount and 17 ft (5.2 m) of PRO-FLEX PLUS low loss cable. Connector available separately.

#### KTMX66\*

Motorola NMO-style mount with 17 ft (5.2 m) PRO-FLEX T with white PVC jacket over TEFLON<sup>®</sup> dielectric. Connector available separately.



\*Available until depleted